

Towards Black-Box Accountable Authority IBE with Short Ciphertexts and Private Keys

Benoît Libert¹ and Damien Vergnaud² * **

¹ Université Catholique de Louvain, Microelectronics Laboratory
Place du Levant, 3 – 1348 Louvain-la-Neuve – Belgium

² Ecole Normale Supérieure – C.N.R.S. – I.N.R.I.A.
45, Rue d’Ulm – 75230 Paris CEDEX 05 – France

Abstract. At Crypto’07, Goyal introduced the concept of *Accountable Authority Identity-Based Encryption* as a convenient tool to reduce the amount of trust in authorities in Identity-Based Encryption. In this model, if the Private Key Generator (PKG) maliciously re-distributes users’ decryption keys, it runs the risk of being caught and prosecuted. Goyal proposed two constructions: the first one is efficient but can only trace well-formed decryption keys to their source; the second one allows tracing obfuscated decryption boxes in a model (called *weak black-box* model) where cheating authorities have no decryption oracle. The latter scheme is unfortunately far less efficient in terms of decryption cost and ciphertext size. The contribution of this paper is to describe a new construction that combines the efficiency of Goyal’s first proposal with a very simple weak black-box tracing mechanism. The proposed scheme is presented in the selective-ID model but readily extends to meet all security properties in the adaptive-ID sense, which is not known to be true for prior black-box schemes.

Keywords. Identity-based encryption, traceability, efficiency.

1 Introduction

Identity-based cryptography, first proposed by Shamir [39], alleviates the need for digital certificates used in traditional public-key infrastructures. In such systems, users’ public keys are public identifiers (*e.g.* email addresses) and the matching private keys are derived by a trusted party called Private Key Generator (PKG). The first practical construction for *Identity-Based Encryption* (IBE) was put forth by Boneh and Franklin [8] – despite the bandwidth-demanding

* The first author acknowledges the Belgian National Fund for Scientific Research (F.R.S.-F.N.R.S.) for their financial support and the BCRYPT Interuniversity Attraction Pole. The second author is supported by the European Commission through the IST Program under Contract ICT-2007-216646 ECRYPT II and by the French *Agence Nationale de la Recherche* through the PACE project.

** This is the full version of a paper with the same title presented in Public Key Cryptography 2009 [31]

proposal by Cocks [17] – and, since then, a large body of work has been devoted to the design of schemes with additional properties or relying on different algorithmic assumptions [23, 5, 6, 35, 41, 7, 21, 13, 9].

In spite of its appealing advantages, identity-based encryption has not undergone rapid adoption as a standard. The main reason is arguably the fact that it requires unconditional trust in the PKG: the latter can indeed decrypt any ciphertext or, even worse, re-distribute users’ private keys. The key escrow problem can be mitigated as suggested in [8] by sharing the master secret among multiple PKGs, but this inevitably entails extra communication and infrastructure. Related paradigms [20, 3] strived to remove the key escrow problem but only did so at the expense of losing the benefit of human-memorizable public keys: these models get rid of escrow authorities but both involve traditional (though not explicitly certified) public keys that are usually less convenient to work with than easy-to-remember public identifiers.

In 2007, Goyal [24] explored a new approach to deter rogue actions from authorities. With the *Accountable Authority Identity-Based Encryption* (A-IBE) primitive, if the PKG discloses a decryption key associated with some identity over the Internet, it runs the risk of being caught and sued by the user. A-IBE schemes achieve this goal by means of an interactive private key generation protocol between the user and the PKG. For each identity, there are exponentially-many families of possible decryption keys. The key generation protocol provides the user with a single decryption key while concealing to the PKG the family that this key belongs to. From this private key, the user is computationally unable to find one from a different family. Hence, for a given identity, a pair of private keys from distinct families serves as evidence of a fraudulent PKG. The latter remains able to passively eavesdrop communications but is discouraged to reveal users’ private keys. Also, users cannot falsely accuse an honest PKG since they are unable to compute a new key from a different family using a given key.

PRIOR WORKS. Two constructions were given in [24]. The first one (that we call *Goyal-1* hereafter) builds on Gentry’s IBE [21] and, while efficient, only allows tracing well-formed decryption keys. This white-box model seems unlikely to suffice in practice since malicious parties can rather release an imperfect and/or obfuscated program that only decrypts with small but noticeable probability. The second scheme of [24] (let us call it *Goyal-2*), which is constructed on the Sahai-Waters fuzzy IBE [35], has a variant providing weak black-box traceability: even an imperfect pirate decryption box can be traced (based on its input/output behavior) back to its source although traceability is only guaranteed against dishonest PKGs that have no decryption oracle in the attack game. However, *Goyal-2* is somewhat inefficient as decryption requires a number of pairing calculations that is linear in the security parameter. For the usually required security level, ciphertexts contain more than 160 group elements and decryption calculates a product of about 160 pairings.

Subsequently, Au *et al.* [4] described another A-IBE scheme providing retrievability (*i.e.*, a property that prevents the PKG from revealing more than one key for a given identity without exposing its master key) but remained in

the white-box model. More recently, Goyal *et al.* [25] modified the *Goyal-2* system using attribute-based encryption techniques [35, 26] to achieve full black-box traceability: unlike *Goyal-2*, the scheme of [25] preserves security against dishonest PKGs that have access to a decryption oracle in the model. While definitely desirable in practice, this property is currently achievable only at the expense of the same significant penalty as in *Goyal-2* [24] in terms of decryption cost and ciphertext size.

OUR CONTRIBUTIONS. We present a very efficient and conceptually simple scheme with weak black-box traceability. We prove its security (in the standard model) under the same assumption as *Goyal-2*. Decryption keys and ciphertexts consist of a constant number of group elements and their length is thus linear in the security parameter λ (instead of quadratic as in *Goyal-2*). Encryption and decryption take $O(\lambda^3)$ -time (w.r.t. $O(\lambda^4)$ in *Goyal-2*) with only two pairing computations as for the latter (against more than 160 in *Goyal-2*).

While presented in the selective-ID security model (where adversaries must choose the identity that will be their prey at the outset of the game) for simplicity, our scheme is easily adaptable to the adaptive-ID model of [8]. In contrast, one of the security properties (*i.e.*, the infeasibility for users to frame innocent PKGs) was only established in the selective-ID setting for known schemes in the black-box model (*i.e.*, *Goyal-2* and its fully black-box extension [25]). Among such schemes, ours thus appears to be the first one that can be tweaked so as to achieve adaptive-ID security against dishonest users.

Our scheme performs almost as well as *Goyal-1* (the main overhead being a long master public key *à la* Waters [41] to obtain the adaptive-ID security). In comparison with the latter, that was only analyzed in a white-box model of traceability, our system provides several other advantages:

- Its security relies on a weaker assumption. So far, the only fully practical A-IBE scheme was resting on assumptions whose strength grows with the number of adversarial queries, which can be as large as 2^{30} as commonly assumed in the literature. Such assumptions are subject to a limited attack [16] that requires a careful adjustment of group sizes (by as much as 50% additional bits) to guarantee a secure use of schemes.
- It remains secure when many users want to run the key generation protocol in a concurrent fashion. *Goyal-1* has a key generation protocol involving zero-knowledge proofs. As its security reductions require to rewind adversaries at each key generation query, security is only guaranteed when the PKG interacts with users sequentially. In inherently concurrent environments like the Internet, key generation protocols should remain secure when executed by many users willing to register at the same time. By minimizing the number of rewinds in reductions, we ensure that our scheme remains secure in a concurrent setting. In these regards, the key generation protocol of *Goyal-2* makes use of oblivious transfers (OT) in sub-protocols. It thus supports concurrency whenever the underlying OT protocol does. As already mentioned however, our scheme features a much better efficiency than *Goyal-2*.

- In a white-box model of traceability, it can be made secure against dishonest PKGs equipped with a decryption oracle³. In the following, we nevertheless focus on the (arguably more interesting) weak black-box traceability aspect.

As an extension to the proceedings version of this paper [31], we also show how to apply the idea of our weak black-box tracing mechanism to Gentry's IBE. The resulting A-IBE system is obtained by bringing a simple modification to the key generation protocol of *Goyal-1* so as to perfectly hide the user's key family from the PKG's view while preserving the efficiency of the whole scheme. Since the resulting system inherits the efficiency of Gentry's IBE and the *Goyal-1* white-box A-IBE, it turns out to be the most efficient weakly black-box A-IBE construction to date. Its (adaptive-ID) security is moreover proved under a tight reduction (albeit under a strong assumption).

Finally, since detecting misbehaving PKGs is an equally relevant problem in IBE primitives and their generalizations, we show how the underlying idea of previous schemes can be applied to one of the most practical identity-based broadcast encryption (IBBE) realizations [10]. We also argue that the same technique similarly applies in the context of attribute-based encryption [35, 26].

ORGANIZATION. In the rest of the paper, section 2 recalls the A-IBE security model defined in [24]. We first analyze the white-box version of our scheme in section 3 and then describe a weak black-box tracing mechanism in section 4. Sections 5 and 6 describe and analyze the extensions of our method to Gentry's IBE and the Boneh-Hamburg IBBE scheme, respectively.

2 Background and Definitions

SYNTACTIC DEFINITION AND SECURITY MODEL. We recall the definition of A-IBE schemes and their security properties as defined in [24].

Definition 1. *An Accountable Authority Identity-Based Encryption scheme (A-IBE) is a tuple (**Setup**, **Keygen**, **Encrypt**, **Decrypt**, **Trace**) of efficient algorithms or protocols such that:*

- **Setup** takes as input a security parameter and outputs a master public key mpk and a matching master secret key msk .
- $\text{Keygen}^{(\text{PKG}, \text{U})}$ is an interactive protocol between the public parameter generator PKG and the user U:
 - the common input to PKG and U are: the master public key mpk and an identity ID for which the decryption key has to be generated;
 - the private input to PKG is the master secret key msk .
 Both parties may use a sequence of private coin tosses as additional inputs. The protocol ends with U receiving a decryption key d_{ID} as his private output.
- **Encrypt** takes as input the master public key mpk , an identity ID and a message m and outputs a ciphertext.

³ We believe that the *Goyal-1* system can also be modified so as to obtain this property.

- **Decrypt** takes as input the master public key mpk , a decryption key d_{ID} and a ciphertext C and outputs a message.
- **Trace** given the master public key mpk , a decryption key d_{ID} , this algorithm outputs a key family number n_F or the special symbol $\perp$ if d_{ID} is ill-formed.

Correctness requires that, for any outputs (mpk, msk) of **Setup**, any plaintext m and any identity ID , whenever $d_{\text{ID}} \leftarrow \text{Keygen}^{(\text{PKG}(\text{msk}), \text{U})}(\text{mpk}, \text{ID})$, we have

$$\begin{aligned} & \text{Trace}(\text{mpk}, d_{\text{ID}}) \neq \perp, \\ & \text{Decrypt}(\text{mpk}, d_{\text{ID}}, \text{Encrypt}(\text{mpk}, \text{ID}, m)) = m. \end{aligned}$$

The above definition is for the white-box setting. In a black-box model, **Trace** takes as input an identity ID , the corresponding user's well-formed private key d_{ID} and a decryption box $\mathbb{D}$ that successfully opens a non-negligible fraction ε of ciphertexts encrypted under ID . The output of **Trace** is either "PKG" or "User" depending on which party is found guilty for having crafted $\mathbb{D}$.

Goyal formalized three security properties for A-IBE schemes. The first one is the standard notion of privacy [8] for IBE systems. As for the other ones, the FindKey game captures the intractability for the PKG to create a decryption key of the same family as the one obtained by the user during the key generation protocol. Finally, the ComputeNewKey game models the infeasibility for users to generate a key $d_{\text{ID}}^{(2)}$ outside the family of the legally obtained one $d_{\text{ID}}^{(1)}$.

Definition 2. An A-IBE scheme is deemed secure if all probabilistic polynomial time (PPT) adversaries have negligible advantage in the following games.

1. **The IND-ID-CCA game.** For any PPT algorithm $\mathcal{A}$, the model considers the following game, where $\lambda \in \mathbb{N}$ is a security parameter:

$\text{Game}_{\mathcal{A}}^{\text{IND-ID-CCA}}(\lambda)$

$(\text{mpk}, \text{msk}) \leftarrow \text{Setup}(\lambda)$
 $(m_0, m_1, \text{ID}^*, s) \leftarrow \mathcal{A}^{\text{Dec,KG}}(\text{find}, \text{mpk})$

$\text{Dec} : (C, \text{ID})$
 $\quad \dashrightarrow \text{Decrypt}(\text{mpk}, \text{msk}, \text{ID}, C);$
 $\text{KG} : \text{ID} \dashrightarrow \text{Keygen}^{(\text{PKG}(\text{msk}), \mathcal{A})}(\text{mpk}, \text{ID})$
 $\quad \quad \quad // \quad \text{ID} \neq \text{ID}^*$

 $d^* \xleftarrow{\$} \{0, 1\}$
 $C^* \leftarrow \text{Encrypt}(\text{mpk}, \text{ID}^*, m_{d^*})$
 $d \leftarrow \mathcal{A}^{\text{Dec,KG}}(\text{guess}, s, C^*)$

$\text{Dec} : (C, \text{ID}) \dashrightarrow \text{Decrypt}(\text{mpk}, \text{msk}, \text{ID}, C);$
 $\quad \quad \quad // \quad (C, \text{ID}) \neq (C^*, \text{ID}^*)$
 $\text{KG} : \text{ID} \dashrightarrow \text{Keygen}^{(\text{PKG}(\text{msk}), \mathcal{A})}(\text{mpk}, \text{ID})$
 $\quad \quad \quad // \quad \text{ID} \neq \text{ID}^*$

return 1 if $d = d^*$ and 0 otherwise.

$\mathcal{A}$'s advantage is measured by $\text{Adv}_{\mathcal{A}}^{\text{CCA}}(\lambda) = |\Pr[\text{Game}_{\mathcal{A}}^{\text{CCA}} = 1] - 1/2|$.

The weaker definition of chosen-plaintext security (IND-ID-CPA) is formalized in the same way in [8] but $\mathcal{A}$ is not granted access to a decryption oracle.

2. **The FindKey game.** Let $\mathcal{A}$ be a PPT algorithm. We consider the following game, where $\lambda \in \mathbb{N}$ is a security parameter:

Game _{$\mathcal{A}$} ^{FindKey}(λ)

$$\begin{aligned}
 &(\text{mpk}, \text{ID}, s_1) \leftarrow \mathcal{A}(\text{setup}, \lambda) \\
 &(d_{\text{ID}}^{(1)}, s_2) \leftarrow \text{Keygen}^{(\mathcal{A}(s_1), \cdot)}(\text{mpk}, \text{ID}) \\
 &d_{\text{ID}}^{(2)} \leftarrow \mathcal{A}(\text{findkey}, s_1, s_2) \\
 &\text{return } 1 \text{ if } \text{Trace}(\text{mpk}, d_{\text{ID}}^{(1)}) = \text{Trace}(\text{mpk}, d_{\text{ID}}^{(2)}) \\
 &\quad 0 \text{ otherwise.}
 \end{aligned}$$

$\mathcal{A}$'s advantage is now defined as $\text{Adv}_{\mathcal{A}}^{\text{FindKey}}(\lambda) = \Pr[\text{Game}_{\mathcal{A}}^{\text{FindKey}} = 1]$.

Here, the adversary $\mathcal{A}$ acts as a cheating PKG and the challenger emulates the honest user. Both parties engage in a key generation protocol where the challenger obtains a private key for an identity ID chosen by $\mathcal{A}$. The latter aims at producing a private key corresponding to ID and belonging to the same family as the key obtained by the challenger in the key generation protocol. Such a successful dishonest PKG could disclose user keys without being caught.

Note that, at the beginning of the experiment, $\mathcal{A}$ generates mpk without revealing the master key msk and the challenger runs a sanity check on mpk .

As noted in [24], it makes sense to provide $\mathcal{A}$ with a decryption oracle that undoes ciphertexts using $d_{\text{ID}}^{(1)}$ (and could possibly leak information on the latter's family) between steps 2 and 3 of the game. We call this enhanced notion FindKey-CCA (as opposed to the weaker one which we call FindKey-CPA).

Finally, in the black-box model, instead of outputting a new key $d_{\text{ID}}^{(2)}$, the dishonest PKG comes up with a decryption box $\mathbb{D}$ that correctly decrypts ciphertexts intended for ID with non-negligible probability ε and wins if the tracing algorithm returns "User" when run on $d_{\text{ID}}^{(1)}$ and with oracle access to $\mathbb{D}$.

3. **The ComputeNewKey game.** For a PPT algorithm $\mathcal{A}$, the model finally considers the following game:

Game _{$\mathcal{A}$} ^{ComputeNewKey}(λ)

$$\begin{aligned}
 &(\text{mpk}, \text{msk}) \leftarrow \text{Setup}(\lambda) \\
 &(d_{\text{ID}^*}^{(1)}, d_{\text{ID}^*}^{(2)}, \text{ID}^*) \leftarrow \mathcal{A}^{\text{KG}}(\text{mpk}) \\
 &\quad \mid \text{KG} : \text{ID} \dashrightarrow \text{Keygen}^{(\text{PKG}(\text{msk}), \mathcal{A})}(\text{mpk}, \text{ID}) \\
 &\text{return } 1 \text{ if } \text{Trace}(\text{mpk}, d_{\text{ID}^*}^{(1)}) \neq \perp \text{ and} \\
 &\quad \text{Trace}(\text{mpk}, d_{\text{ID}^*}^{(2)}) \notin \{\perp, \text{Trace}(\text{mpk}, d_{\text{ID}^*}^{(1)})\} \\
 &\quad 0 \text{ otherwise.}
 \end{aligned}$$

$\mathcal{A}$'s advantage is $\text{Adv}_{\mathcal{A}}^{\text{ComputeNewKey}}(\lambda) = \Pr[\text{Game}_{\mathcal{A}}^{\text{ComputeNewKey}} = 1]$.

The ComputeNewKey game involves an adversary interacting with a PKG in executions of the key generation protocol and obtaining private keys associated with *distinct* identities of her choosing. The adversary is declared successful if, for some identity that may have been queried for key generation, she is able to find *two* private keys from *distinct* families. Such a pair would allow her to trick a judge into wrongly believing in a misbehavior of the PKG.

In the black-box scenario, the output of the dishonest user consist of a key $d_{\text{ID}^*}^{(1)}$ and a pirate decryption box $\mathbb{D}$ that yields the correct answer with probability ε when provided with a ciphertext encrypted for ID^* . In this case, the adversary wins if the output of $\mathbf{Trace}^{\mathbb{D}}(\text{mpk}, d_{\text{ID}^*}^{(1)})$ is “PKG”.

In [14], Canetti, Halevi and Katz suggested relaxed notions of IND-ID-CCA and IND-ID-CPA security where the adversary has to choose the target identity ID^* ahead of time (even before seeing the master public key mpk). This relaxed model, called “selective-ID” model (or IND-sID-CCA and IND-sID-CPA for short), can be naturally extended to the ComputeNewKey notion.

BILINEAR MAPS AND COMPLEXITY ASSUMPTIONS. We use prime order groups $(\mathbb{G}, \mathbb{G}_T)$ endowed with an efficiently computable map $e : \mathbb{G} \times \mathbb{G} \rightarrow \mathbb{G}_T$ such that:

1. $e(g^a, h^b) = e(g, h)^{ab}$ for any $(g, h) \in \mathbb{G} \times \mathbb{G}$ and $a, b \in \mathbb{Z}$;
2. $e(g, h) \neq 1_{\mathbb{G}_T}$ whenever $g, h \neq 1_{\mathbb{G}}$.

In such *bilinear groups*, we assume the hardness of the (now classical) Decision Bilinear Diffie-Hellman problem that has been widely used in the recent years.

Definition 3. Let $(\mathbb{G}, \mathbb{G}_T)$ be bilinear groups of prime order p and $g \in \mathbb{G}$. The **Decision Bilinear Diffie-Hellman Problem (DBDH)** is to distinguish the distributions of tuples $(g^a, g^b, g^c, e(g, g)^{abc})$ and $(g^a, g^b, g^c, e(g, g)^z)$ for random values $a, b, c, z \xleftarrow{\$} \mathbb{Z}_p^*$. The advantage of a distinguisher $\mathcal{B}$ is measured by

$$\begin{aligned} \text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{\text{DBDH}}(\lambda) = & \left| \Pr[a, b, c \xleftarrow{\$} \mathbb{Z}_p^* : \mathcal{B}(g^a, g^b, g^c, e(g, g)^{abc}) = 1] \right. \\ & \left. - \Pr[a, b, c, z \xleftarrow{\$} \mathbb{Z}_p^* : \mathcal{B}(g^a, g^b, g^c, e(g, g)^z) = 1] \right|. \end{aligned}$$

For convenience, we use an equivalent formulation – called *modified* DBDH – of the problem which is to distinguish $e(g, g)^{ab/c}$ from random given (g^a, g^b, g^c) .

3 The Basic Scheme

The scheme mixes ideas from the “commutative-blinding” [5] and “exponent-inversion” [36] frameworks. Private keys have the same shape as in commutative-blinding-based schemes [5, 6, 41, 13]. At the same time, their first element is a product of two terms, the first one of which is inspired from Gentry’s IBE [21].

According to a technique applied in [24], private keys contain a family number t that cannot be tampered with while remaining hidden from the PKG. This family number t is determined by combining two random values t_0 and t_1 respectively chosen by the user and the PKG in the key generation protocol. The

latter begins with the user sending a commitment R to t_0 . Upon receiving R , the PKG turns it into a commitment to $t_0 + t_1$ and uses the modified commitment to generate a “blinded” private key d'_{ID} . The user obtains his final key d_{ID} by “unblinding” d'_{ID} thanks to the randomness that was used to compute R .

A difference with *Goyal-1* is that the key family number is perfectly hidden to the PKG and the FindKey-CPA security is unconditional. In the key generation protocol, the user’s first message is a perfectly hiding commitment that comes along with a witness-indistinguishable (WI) proof of knowledge of its opening. In *Goyal-1*, users rather send a deterministic (and thus non-statistically hiding) commitment and knowledge of the underlying value must be proven in zero-knowledge because a proof of knowledge of a discrete logarithm must be simulated (by rewinding the adversary) in the proof of FindKey-CPA security. In the present scheme, the latter does not rely on a specific assumption and we do not need to simulate knowing the solution of a particular problem instance. Therefore, we can dispense with perfectly ZK proofs and settle for a more efficient 3-move WI proof (such as Okamoto’s variant [33] of Schnorr [38]) whereas 4 rounds are needed using zero-knowledge proofs of knowledge.

3.1 Description

Setup: given $\lambda \in \mathbb{N}$, the PKG selects bilinear groups $(\mathbb{G}, \mathbb{G}_T)$ of prime order $p > 2^\lambda$ with a random generator $g \xleftarrow{\$} \mathbb{G}$. It chooses $h, Y, Z \xleftarrow{\$} \mathbb{G}$ and $x \xleftarrow{\$} \mathbb{Z}_p^*$ at random. It defines its master key as $\text{msk} := x$ and the master public key is chosen as $\text{mpk} := (X = g^x, Y, Z, h)$.

Keygen^(PKG,U) : to obtain a private key for his identity ID, a user U interacts with the PKG in the following key generation protocol.

1. The user U draws $t_0, \theta \xleftarrow{\$} \mathbb{Z}_p^*$, provides the PKG with a commitment $R = h^{t_0} \cdot X^\theta$ and also gives an interactive witness indistinguishable proof of knowledge of the pair (t_0, θ) , which he retains for later use.
2. The PKG outputs $\perp$ if the proof of knowledge fails to verify. Otherwise, it picks $r', t_1 \xleftarrow{\$} \mathbb{Z}_p^*$ and returns

$$d'_{\text{ID}} = (d'_1, d'_2, d'_3) = \left((Y \cdot R \cdot h^{t_1})^{1/x} \cdot (g^{\text{ID}} \cdot Z)^{r'}, X^{r'}, t_1 \right). \quad (1)$$

3. U picks $r'' \xleftarrow{\$} \mathbb{Z}_p^*$ and computes $d_{\text{ID}} = (d'_1/g^\theta \cdot (g^{\text{ID}} \cdot Z)^{r''}, d'_2 \cdot X^{r''}, d'_3 + t_0)$ which should equal

$$d_{\text{ID}} = (d_1, d_2, d_3) = \left((Y \cdot h^{t_0+t_1})^{1/x} \cdot (g^{\text{ID}} \cdot Z)^r, X^r, t_0 + t_1 \right) \quad (2)$$

where $r = r' + r''$. Then, U checks whether d_{ID} satisfies the relation

$$e(d_1, X) = e(Y, g) \cdot e(h, g)^{d_3} \cdot e(g^{\text{ID}} \cdot Z, d_2). \quad (3)$$

If so, he sets his private key as d_{ID} and the latter belongs to the family of decryption keys identified by $n_F = d_3 = t_0 + t_1$. He outputs $\perp$ otherwise.

Encrypt: to encrypt $m \in \mathbb{G}_T$ given mpk and ID , choose $s \xleftarrow{\$} \mathbb{Z}_p^*$ and compute

$$C = (C_1, C_2, C_3, C_4) = (X^s, (g^{\text{ID}} \cdot Z)^s, e(g, h)^s, m \cdot e(g, Y)^s).$$

Decrypt: given $C = (C_1, C_2, C_3, C_4)$ and $d_{\text{ID}} = (d_1, d_2, d_3)$, compute

$$m = C_4 \cdot \left(\frac{e(C_1, d_1)}{e(C_2, d_2) \cdot C_3^{d_3}} \right)^{-1} \quad (4)$$

Trace: given a purported private key $d_{\text{ID}} = (d_1, d_2, d_3)$ and an identity ID , check the validity of d_{ID} w.r.t. ID using relation (3). If valid, d_{ID} is declared as a member of the family identified by $n_F = d_3$.

The correctness of the scheme follows from the fact that well-formed private keys always satisfy relation (3). By raising both members of (3) to the power $s \in \mathbb{Z}_p^*$, we see that the quotient of pairings in (11) actually equals $e(g, Y)^s$.

The scheme features about the same efficiency as classical IBE schemes derived from the commutative-blinding framework [5]. Encryption demands no pairing calculation since $e(g, h)$ and $e(g, Y)$ can both be cached as part of the system parameters. Decryption requires to compute a quotient of two pairings which is significantly faster than two independent pairing evaluations when optimized in the same way as modular multi-exponentiations.

In comparison with the most efficient standard model scheme based on the same assumption (which is currently the first scheme of [5]), the only overhead is a slightly longer ciphertext and an extra exponentiation in $\mathbb{G}_T$ at both ends.

3.2 Security

SELECTIVE-ID SECURITY. We first prove the IND-sID-CPA security under the modified DBDH assumption (mDBDH).

Theorem 1. *The scheme is IND-sID-CPA under the mDBDH assumption.*

Proof. We show how a simulator $\mathcal{B}$ can interact with a selective-ID adversary $\mathcal{A}$ to solve a mDBDH instance $(T_a = g^a, T_b = g^b, T_c = g^c, T \stackrel{?}{=} e(g, g)^{ab/c})$. At the outset of the game, $\mathcal{A}$ announces the target identity ID^* . To prepare mpk , $\mathcal{B}$ chooses $\alpha, \gamma, t^* \xleftarrow{\$} \mathbb{Z}_p^*$ and sets $X = T_c = g^c$, $h = T_b = g^b$, $Y = X^\gamma \cdot h^{-t^*}$, and $Z = g^{-\text{ID}^*} \cdot X^\alpha$. The adversary's view is simulated as follows.

Queries: at any time, $\mathcal{A}$ may trigger an execution of the key generation protocol for an identity $\text{ID} \neq \text{ID}^*$ of her choosing. She then supplies an element $R = h^{t_0} \cdot X^\theta$ along with a WI proof of knowledge of (t_0, θ) . The simulator $\mathcal{B}$ verifies the proof but does not need to rewind the adversary as it can answer the query without knowing (t_0, θ) . To do so, it picks $t_1 \xleftarrow{\$} \mathbb{Z}_p^*$ at random and defines $W = Y \cdot R \cdot h^{t_1}$, $d'_3 = t_1$. Elements d'_1 and d'_2 are generated as

$$(d'_1, d'_2) = \left((g^{\text{ID}} \cdot Z)^{r'} \cdot W^{-\frac{\alpha}{\text{ID} - \text{ID}^*}}, X^{r'} \cdot W^{-\frac{1}{\text{ID} - \text{ID}^*}} \right) \quad (5)$$

using a random $r' \xleftarrow{\$} \mathbb{Z}_p^*$. If we set $\tilde{r}' = r' - \frac{w}{c(\text{ID} - \text{ID}^*)}$, where $w = \log_g(W)$, we observe that (d'_1, d'_2) has the correct distribution since

$$\begin{aligned} W^{1/c} \cdot (g^{\text{ID}} \cdot Z)^{\tilde{r}'} &= W^{1/c} \cdot (g^{\text{ID} - \text{ID}^*} \cdot X^\alpha)^{\tilde{r}'} \\ &= W^{1/c} \cdot (g^{\text{ID} - \text{ID}^*} \cdot X^\alpha)^{r'} \cdot (g^{\text{ID} - \text{ID}^*})^{-\frac{w}{c(\text{ID} - \text{ID}^*)}} \cdot X^{-\frac{w\alpha}{c(\text{ID} - \text{ID}^*)}} \\ &= (g^{\text{ID}} \cdot Z)^{r'} \cdot W^{-\frac{\alpha}{\text{ID} - \text{ID}^*}} \end{aligned}$$

and $X^{\tilde{r}'} = X^{r'} \cdot (g^c)^{-\frac{w}{c(\text{ID} - \text{ID}^*)}} = X^{r'} \cdot W^{-\frac{1}{\text{ID} - \text{ID}^*}}$. Finally, the “partial private key” (d'_1, d'_2, d'_3) is returned to $\mathcal{A}$. Note that the above calculation can be carried out without knowing $w = \log_g(W)$ or the representation (t_0, θ) of R w.r.t. to (h, X) and $\mathcal{B}$ does *not* need to rewind $\mathcal{A}$.

Challenge: when the first stage is over, $\mathcal{A}$ outputs $m_0, m_1 \in \mathbb{G}_T$. At this point, $\mathcal{B}$ picks $r^* \xleftarrow{\$} \mathbb{Z}_p^*$ and defines a private key $(d_1, d_2, d_3) = (g^\gamma \cdot X^{\alpha r^*}, X^{r^*}, t^*)$ for the identity ID^* . It flips a fair coin $d^* \xleftarrow{\$} \{0, 1\}$ and encrypts m_{d^*} as

$$C_1^* = T_a = g^a \quad C_2^* = T_a^\alpha \quad C_3^* = T \quad C_4^* = m_{d^*} \cdot \frac{e(C_1^*, d_1)}{e(C_2^*, d_2) \cdot C_3^{*d_3}}.$$

We see that (d_1, d_2, d_3) is a valid key for ID^* . Since $g^{\text{ID}^*} \cdot Z = X^\alpha = T_c^\alpha$ and $h = g^b$, $C^* = (C_1^*, C_2^*, C_3^*, C_4^*)$ is a valid encryption of m_{d^*} (with the exponent $s = a/c$) if $T = e(g, g)^{ab/c}$. If T is random, we have $T = e(g, h)^{s'}$ for some random $s' \in \mathbb{Z}_p^*$ and thus $C_4^* = m_{d^*} \cdot e(Y, g)^s \cdot e(g, h)^{(s-s')t^*}$, which means that m_{d^*} is perfectly hidden since t^* is independent of $\mathcal{A}$'s view.

As usual, $\mathcal{B}$ outputs 1 (meaning that $T = e(g, g)^{ab/c}$) if $\mathcal{A}$ successfully guesses $d' = d^*$ and 0 otherwise. $\square$

In the above proof, the simulator does not rewind the adversary at any time. The scheme thus remains IND-sID-CPA in concurrent environments, where a batch of users may want to simultaneously run the key generation protocol.

Also, the simulator knows a valid private key for each identity. This allows using hash proof systems [18, 19] as in [21, 29] to secure the scheme against chosen-ciphertext attacks. The advantage of this approach, as shown in appendices A and C, is to provide FindKey-CCA security in a white-box setting.

Unlike the *Goyal-1* scheme, the basic system provides unconditional FindKey-CPA security: after an execution of the key generation protocol, even an all powerful PKG does not have any information on the component d_3 that is eventually part of the private key obtained by the new user.

Theorem 2. *In the information theoretic sense, no adversary has an advantage in the FindKey-CPA game.*

Proof. The proof directly follows from the perfect hiding property of Pedersen's commitment [34] and the perfect witness indistinguishability of the protocol [33] for proving knowledge of a discrete logarithm representation. Since the commitment $R = h^{t_0} \cdot X^\theta$ and the proof of knowledge of (t_0, θ) perfectly hide t_0 to the PKG, all elements of $\mathbb{Z}_p^*$ are equally likely values of $d_3 = t_0 + t_1$ as for the last part of the user's eventual private key. $\square$

The original version of the paper [31] describes a hybrid variant of the scheme that provides white-box FindKey-CCA security using authenticated symmetric encryption in the fashion of [30, 40, 27] so as to reject all invalid ciphertexts with high probability. In this version, we only consider schemes with the weak black-box traceability property.

Theorem 3. *In the selective-ID ComputeNewKey game, any PPT adversary has negligible advantage assuming that the Diffie-Hellman assumption holds.*

Proof. For simplicity, we prove the result using an equivalent formulation of the Diffie-Hellman problem which is to find $h^{1/x}$ given $(g, h, X = g^x)$.

At the outset of the game, $\mathcal{A}$ declares the identity ID^* for which she aims at finding two private keys $d_{\text{ID}^*}^{(1)}, d_{\text{ID}^*}^{(2)}$ comprising distinct values of $d_3 = t$. Then, the simulator $\mathcal{B}$ prepares the PKG's public key as follows. Elements h and X are taken from the modified Diffie-Hellman instance (g, h, X) . As in the proof of theorem 1, $\mathcal{B}$ defines $Z = g^{-\text{ID}^*} \cdot X^\alpha$ for a randomly chosen $\alpha \xleftarrow{\$} \mathbb{Z}_p^*$. To define Y , it chooses random values $\gamma, t'_1 \xleftarrow{\$} \mathbb{Z}_p^*$ and sets $Y = X^\gamma \cdot h^{-t'_1}$.

Queries: in this game, $\mathcal{A}$ is allowed to query executions of the key generation protocol w.r.t. any identity, including ID^* . The only requirement is that queried identities be distinct.

- For an identity $\text{ID} \neq \text{ID}^*$, $\mathcal{B}$ can proceed *exactly* as suggested by relation (5) in the proof of theorem 1 and does not need to rewind $\mathcal{A}$.
- When $\text{ID} = \text{ID}^*$, $\mathcal{B}$ conducts the following steps. When $\mathcal{A}$ supplies a group element $R = h^{t_0} \cdot X^\theta$ along with a WI proof of knowledge of (t_0, θ) , $\mathcal{B}$ uses the knowledge extractor of the proof of knowledge that allows extracting a representation (t_0, θ) of R by rewinding $\mathcal{A}$. Next, $\mathcal{B}$ computes $t_1 = t'_1 - t_0$ picks $r \xleftarrow{\$} \mathbb{Z}_p^*$ and returns

$$(d'_1, d'_2, d'_3) = (g^{\gamma+\theta} \cdot (g^{\text{ID}^*} \cdot Z)^r, X^r, t_1). \quad (6)$$

To see that the above tuple has the appropriate shape, we note that

$$(Y \cdot R \cdot h^{t_1})^{1/x} = (Y \cdot h^{t_0+t_1} \cdot X^\theta)^{1/x} = (Y \cdot h^{t'_1} \cdot X^\theta)^{1/x} = g^{\gamma+\theta}.$$

Output: upon its termination, $\mathcal{A}$ is expected to come up with distinct valid private keys $d_{\text{ID}^*}^{(1)} = (d_1^{(1)}, d_2^{(1)}, d_3^{(1)})$ and $d_{\text{ID}^*}^{(2)} = (d_1^{(2)}, d_2^{(2)}, d_3^{(2)})$, such that $t = d_3^{(1)} \neq d_3^{(2)} = t'$, for the identity ID^* . Given that we must have

$$\begin{aligned} d_1^{(1)} &= (Y \cdot h^t)^{1/x} \cdot X^{\alpha r} & d_2^{(1)} &= X^r \\ d_1^{(2)} &= (Y \cdot h^{t'})^{1/x} \cdot X^{\alpha r'} & d_2^{(2)} &= X^{r'} \end{aligned}$$

for some values $r, r' \in \mathbb{Z}_p$, $\mathcal{B}$ can extract $h^{1/x} = \left(\frac{d_1^{(1)}/d_2^{(1)\alpha}}{d_1^{(2)}/d_2^{(2)\alpha}} \right)^{\frac{1}{t-t'}}.$ $\square$

We note that, in the above proof, the simulator does not have to rewind all executions of the key generation protocol but only one, when the adversary asks for a private key corresponding to the target identity ID^* (recall that all queries involve distinct identities). Given that the number of rewinds is constant, the proof still goes through when the simulator is presented with many concurrent key generation queries. If other executions of the protocol (that necessarily involve identities $ID \neq ID^*$) are nested within the one being rewinded when dealing with ID^* , the simulator simply runs them as an honest verifier would in the proof of knowledge and calculates the PKG's output as per relation (5) in the proof of theorem 1. Thus, the initial rewind does not trigger any other one and the simulation still takes polynomial time in a concurrent setting.

ADAPTIVE-ID SECURITY. The scheme can obviously be made IND-ID-CPA if Waters' "hash function" $F(ID) = u' \prod_{j=1}^n u_i^{i_j}$ – where $ID = i_1 \dots i_n \in \{0, 1\}^n$ and $(u', u_1, \dots, u_n) \in \mathbb{G}^{n+1}$ is part of mpk – supersedes the Boneh-Boyen identity hashing $F(ID) = g^{ID} \cdot Z$. The number theoretic hash function F is chosen so as to equal $F(ID) = g^{J_1(ID)} \cdot X^{J_2(ID)}$ for integer-valued functions J_1, J_2 that are computable by the simulator. The security proof relies on the fact that J_1 is small in absolute value and cancels with non-negligible probability proportional to $1/q(n+1)$, where q is the number of key generation queries.

When extending the proof of theorem 3 to the adaptive setting, an adversary with advantage ε allows solving CDH with probability $\varepsilon/8q^2(n+1)$. The reason is that the simulator has to guess beforehand which key generation query will involve the target identity ID^* . If ID^* is expected to appear in the j^{th} query, when the latter is made, $\mathcal{B}$ rewinds $\mathcal{A}$ to extract (t_0, θ) and uses the special value t'_1 to answer the query as per (6). With probability $1/q$, $\mathcal{B}$ is fortunate when choosing $j \xleftarrow{\$} \{1, \dots, q\}$ at the beginning and, again, $J_1(ID^*)$ happens to cancel with probability $1/8q(n+1)$ for the target identity.

4 Weak Black-Box Traceability

Theorem 3 showed the infeasibility for users to compute another key from a different family given their private key. In these regards, a decryption key implements a "1-copyrighted function" – in the terminology of [32, 28] – for the matching identity. Using this property and the perfect white-box FindKey-CPA security, we describe a black-box tracing mechanism that protects the user from a dishonest PKG as long as the latter is withheld access to a decryption oracle.

The tracing strategy is close to the one used by Kiayias and Yung [28] in 2-user traitor tracing schemes, where the tracer determines which one out of two subscribers produced a pirate decoder. In our setting, one rather has to decide whether an ε -useful decryption device stems from the PKG or the user himself.

Trace ^{$\mathbb{D}$} (mpk, d_{ID} , ε): given a well-formed private key $d_{ID} = (d_1, d_2, d_3)$ belonging to a user of identity ID and oracle access to a decoder $\mathbb{D}$ that decrypts ciphertexts encrypted for ID with probability ε , conduct the following steps.

- a. Initialize a counter $ctr \leftarrow 0$ and repeat the next steps $L = 16\lambda/\varepsilon$ times:

1. Choose distinct exponents $s, s' \xleftarrow{\$} \mathbb{Z}_p^*$ at random, compute $C_1 = X^s$, $C_2 = (g^{\text{ID}} \cdot Z)^s$ and $C_3 = e(g, h)^{s'}$.
 2. Calculate $C_4 = m \cdot e(C_1, d_1) / (e(C_2, d_2) \cdot C_3^{d_3})$ for a randomly chosen message $m \in \mathbb{G}_T$.
 3. Feed the decryption device $\mathbb{D}$ with (C_1, C_2, C_3, C_4) . If $\mathbb{D}$ outputs $m' \in \mathbb{G}_T$ such that $m' = m$, increment ctr .
- b. If $ctr = 0$, incriminate the PKG. Otherwise, incriminate the user.

The soundness of this algorithm is proved using a similar technique to [1]. To ensure the independence of iterations, we assume (as in [1]) that pirate devices are stateless, or resettable, and do not retain information from prior queries: each decryption query is answered as if it were the first one and, in particular, the pirate device cannot self-destruct.

Theorem 4. *Under the mDBDH assumption, dishonest users have negligible chance to produce a decryption device $\mathbb{D}$ that makes the tracing algorithm incriminate the PKG in the selective-ID ComputeNewKey game.*

Proof. The tracing algorithm points to the PKG if it ends up with $ctr = 0$. The variable ctr can be seen as the sum of $L = 16\lambda/\varepsilon$ independent random variables $X_i \in \{0, 1\}$ having the same expected value p_1 . We have $\mu = \mathbf{E}[ctr] = Lp_1$. The Chernoff bound tells us that, for any real number ω such that $0 \leq \omega \leq 1$, $\Pr[ctr < (1-\omega)\mu] < \exp(-\mu\omega^2/2)$. Under the mDBDH assumption, we certainly have $\mathbf{Adv}^{\text{mDBDH}}(\lambda) \leq \varepsilon/2$ (since $\varepsilon/2$ is presumably non-negligible). Lemma 1 shows that $p_1 \geq \varepsilon - \mathbf{Adv}^{\text{mDBDH}}(\lambda)$, which implies

$$\mu = Lp_1 \geq L(\varepsilon - \mathbf{Adv}^{\text{mDBDH}}(\lambda)) \geq \frac{L\varepsilon}{2} = 8\lambda. \quad (7)$$

With $\omega = 1/2$, the Chernoff bound guarantees that

$$\Pr[ctr < 1] < \Pr[ctr < 4\lambda] = \Pr[ctr < \mu/2] < \exp(-\mu/8) = \exp(-\lambda).$$

□

Lemma 1. *In the selective-ID ComputeNewKey game, if $\mathbb{D}$ correctly opens well-formed ciphertexts with probability ε , the probability that an iteration of the tracing algorithm increases ctr is at least $p_1 \geq \varepsilon - \mathbf{Adv}^{\text{mDBDH}}(\lambda)$.*

Proof. We consider two games called Game₀ and Game₁ where the adversary $\mathcal{A}$ is faced with a ComputeNewKey challenger $\mathcal{B}$ and produces a decryption device $\mathbb{D}$ which is provided with ciphertexts during a tracing stage. In Game₀, $\mathbb{D}$ is given a properly formed encryption of some plaintext m whereas it is given a ciphertext C where C_3 has been changed in Game₁. In either case, we call p_i (with $i \in \{0, 1\}$) the probability that $\mathbb{D}$ returns the plaintext m chosen by $\mathcal{B}$.

In the beginning of Game₀, $\mathcal{A}$ chooses a target identity ID^* and $\mathcal{B}$ defines the system parameters as $X = g^c$, $h = g^b$, $Y = X^\gamma \cdot h^{-t^*}$ and $Z = g^{-\text{ID}^*} \cdot X^\alpha$ for random $\alpha, \gamma, t^* \xleftarrow{\$} \mathbb{Z}_p^*$. Then, $\mathcal{A}$ starts making key generation queries that are

treated using the same technique as in the proof of theorem 3. Again, $\mathcal{B}$ only has to rewind the WI proof when the query pertains to ID^* .

At the end of the game, $\mathcal{A}$ outputs a decryption box $\mathbb{D}$ that correctly decrypts a fraction ε of ciphertexts. Then, $\mathcal{B}$ constructs a ciphertext C as

$$C_1 = g^a, \quad C_2 = (g^a)^\alpha, \quad C_3 = T, \quad C_4 = m \cdot \frac{e(C_1, d_1)}{e(C_2, d_2) \cdot C_3^{t^*}}$$

where $T \in \mathbb{G}_T$.

In Game_0 , $\mathcal{B}$ sets $T = e(g, g)^{ab/c}$ so that we have $C_3 = e(g, h)^{a/c}$ and C is a valid ciphertext (for the encryption exponent $s = a/c$) that $\mathbb{D}$ correctly decrypts with probability ε . In this case, $\mathbb{D}$ thus outputs $m' = m \in \mathbb{G}_T$ with probability $p_0 = \varepsilon$. In Game_1 , T is chosen as a random element of $\mathbb{G}_T$ and $C = (C_1, C_2, C_3, C_4)$ has the distribution of a ciphertext produced by the tracing stage and $\mathbb{D}$ must output a plaintext $m' = m$ with probability p_1 . It is clear that $|p_0 - p_1| \leq \mathbf{Adv}^{\text{mDBDH}}(\lambda)$ and we thus have $p_1 \geq \varepsilon - \mathbf{Adv}^{\text{mDBDH}}(\lambda)$. $\square$

The proofs of theorem 4 and lemma 1 extend to the adaptive-ID setting using the same arguments as in the last paragraph of section 3. As mentioned in the remark at the end of section 3.2 in section 3, proving adaptive-ID white-box security against dishonest users incurs a quadratic degradation factor in the number of adversarial queries. When transposing the proof of lemma 1 to the adaptive-ID model, we are faced with the same quadratic degradation in q and the bound on p_1 becomes $p_1 \geq \varepsilon - 8 \cdot q^2(n+1) \cdot \mathbf{Adv}^{\text{mDBDH}}(\lambda)$. The proof of theorem 4 goes through as long as $\varepsilon \geq 16 \cdot q^2 \cdot (n+1) \cdot \mathbf{Adv}^{\text{mDBDH}}(\lambda)$ (so that $p_1 \geq \varepsilon/2$). Since q is polynomial, this is asymptotically the case since $q^2 \cdot (n+1) \cdot \mathbf{Adv}^{\text{mDBDH}}(\lambda)$ remains negligible under the mDBDH assumption.

The system turns out to be the first scheme that is amenable for weak black-box traceability against dishonest users in the adaptive-ID sense. Due to their reliance on attribute-based encryption techniques (for which only selective-ID adversaries were dealt with so far), earlier (weak) black-box A-IBE proposals [24, 25] are only known to provide selective-ID security against dishonest users.

As for the security against dishonest PKGs, we observed that, in the FindKey-CPA game, the last part $d_3^{(1)} = t$ of the user's private key is perfectly hidden to the malicious PKG after the key generation protocol. Then, a pirate decoder $\mathbb{D}$ made by the PKG has negligible chance of decrypting ciphertexts where C_3 is random in the same way as the user would. When the user comes across $\mathbb{D}$ and takes it to the court, the latter runs the tracing algorithm using $\mathbb{D}$ and the user's well-formed key $d_{\text{ID}}^{(1)} = (d_1^{(1)}, d_2^{(1)}, d_3^{(1)})$ for which $d_3^{(1)}$ is independent of $\mathbb{D}$.

Lemma 2. *In the FindKey-CPA game, one iteration of the tracing algorithm increases ctr with probability at most $1/p$.*

Proof. In an iteration of the tracing stage, $\mathbb{D}$ is given $C = (C_1, C_2, C_3, C_4)$ such that $C_1 = X^s$, $C_2 = (g^{\text{ID}} \cdot Z)^s$, $C_3 = e(g, h)^{s'}$ and $C_4 = m \cdot e(g, Y)^s \cdot e(g, h)^{(s-s')t}$ for distinct $s, s' \xleftarrow{\$} \mathbb{Z}_p^*$. Since $\mathbb{D}$ has no information on $d_3^{(1)} = t$, for any plaintext $m \in \mathbb{G}_T$, there is a value $d_3^{(1)}$ that explains C_4 and it comes that $\mathbb{D}$ returns the one chosen by the tracer with probability $1/p$. $\square$

We note that a pirate device $\mathbb{D}$ generated by the dishonest PKG is able to recognize invalid ciphertexts in the tracing stage (as it may contain the master secret x). However, as long as $\mathbb{D}$ is assumed stateless, it cannot shutdown or self-destruct when detecting a tracing attempt. Moreover, with all but negligible probability, it will never be able to decrypt such invalid ciphertexts in the same way as the owner of $d_{\mathbb{D}}^{(1)}$ would.

Theorem 5. *In the black-box FindKey-CPA game, a dishonest PKG has negligible advantage.*

Proof. The dishonest PKG is not detected if it outputs a decryption box for which the tracing ends with a non-zero value of ctr . From lemma 2, it easily comes that $\Pr[ctr \neq 0] = \Pr[ctr \geq 1] \leq L/p = 16\lambda/(\varepsilon p) \leq 16\lambda/(2^\lambda \varepsilon)$. $\square$

To secure the scheme against chosen-ciphertext attacks and preserve the weak black-box property, we can use the Canetti-Halevi-Katz [15] technique or its optimizations [11, 12] that do not affect the tracing algorithm.

5 Extension to Gentry's IBE

In this section, we show how to apply the weak black-box tracing mechanism of section 4 to Gentry's IBE. The resulting A-IBE system is obtained by bringing a simple modification to the key generation protocol of Goyal's first scheme [24] so as to perfectly hide the user's key family from the PKG's view while preserving the efficiency of the whole scheme.

The advantage of this scheme is to directly provide adaptive-ID security against dishonest users and under reductions that are just as tight as in Gentry's system. This benefit comes at the expense of sacrificing the concurrent security of the key generation protocol (as security proofs require to rewind at each key generation query) and relying on a somewhat strong assumption.

Definition 4 ([21]). *In bilinear groups $(\mathbb{G}, \mathbb{G}_T)$, the q -Decision Augmented Bilinear Diffie-Hellman Exponent Problem (q -ADBDHE) is to distinguish the distribution $(g, g^\alpha, \dots, g^{(\alpha^q)}, h, h^{(\alpha^{q+2})}, e(g, h)^{(\alpha^{q+1})})$ from the distribution $(g, g^\alpha, \dots, g^{(\alpha^q)}, h, h^{(\alpha^{q+2})}, e(g, h)^\beta)$, where $\alpha, \beta \xleftarrow{\$} \mathbb{Z}_p^*$ and $h \xleftarrow{\$} \mathbb{G}^*$. The advantage $\text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{q\text{-ADBDHE}}(\lambda)$ of a distinguisher $\mathcal{B}$ is defined as in definition 5*

In the description hereafter, the encryption and decryption algorithms are exactly as in [21]. Since the key generation protocol perfectly conceals the user's key family, we can apply the same weak black-box tracing mechanism as in section 4. The resulting system turns out to be the most efficient adaptive-ID secure weakly black-box A-IBE to date.

Setup: given a security parameter $\lambda \in \mathbb{N}$, the PKG chooses bilinear groups $(\mathbb{G}, \mathbb{G}_T)$ of order $p > 2^\lambda$ with a generator $g \xleftarrow{\$} \mathbb{G}$. It picks $h, g \xleftarrow{\$} \mathbb{G}$ and $\alpha \xleftarrow{\$} \mathbb{Z}_p^*$ at random. It defines the master key as $\text{msk} := \alpha$ and the master public key is defined to be $\text{mpk} := (g, g_1 = g^\alpha, h)$.

Keygen^(PKG,U) : the user U and the PKG interact in the following protocol.

1. U picks $t_0, \theta \xleftarrow{\$} \mathbb{Z}_p^*$ and sends a commitment $R = g^{-t_0} \cdot (g_1 \cdot g^{-\text{ID}})^\theta$ to the PKG. He also gives an interactive witness indistinguishable proof of knowledge of the pair (t_0, θ) .
2. The PKG outputs $\perp$ if the proof of knowledge is invalid. Otherwise, it picks $t_1 \xleftarrow{\$} \mathbb{Z}_p^*$ and returns

$$d'_{\text{ID}} = (d', t'_{\text{ID}}) = \left((h \cdot R \cdot g^{-t_1})^{1/(\alpha - \text{ID})}, t_1 \right). \quad (8)$$

3. U computes $d_{\text{ID}} = (d'/g^\theta, t'_{\text{ID}} + t_0)$ which should equal

$$d_{\text{ID}} = (d, t_{\text{ID}}) = \left((h \cdot g^{-(t_0+t_1)})^{1/(\alpha - \text{ID})}, t_0 + t_1 \right). \quad (9)$$

Then, U checks whether d_{ID} satisfies the relation

$$e(d, g_1 \cdot g^{-\text{ID}}) = e(h, g) \cdot e(g, g)^{-t_{\text{ID}}}. \quad (10)$$

If so, he sets his private key as d_{ID} , which belongs to the key family identified by $n_F = t_{\text{ID}} = t_0 + t_1$. He outputs $\perp$ otherwise.

Encrypt: to encrypt $m \in \mathbb{G}_T$ given mpk and ID , choose $s \xleftarrow{\$} \mathbb{Z}_p^*$ and compute

$$C = (C_1, C_2, C_3) = \left((g_1 \cdot g^{-\text{ID}})^s, e(g, g)^s, m \cdot e(g, h)^s \right).$$

Decrypt: given $C = (C_1, C_2, C_3)$ and $d_{\text{ID}} = (d, t_{\text{ID}})$, compute

$$m = C_3 \cdot \left(e(C_1, d) \cdot C_2^{t_{\text{ID}}} \right)^{-1}$$

Trace ^{$\mathbb{D}$} ($\text{mpk}, d_{\text{ID}}, \varepsilon$): given a valid private key $d_{\text{ID}} = (d, t_{\text{ID}})$ belonging to user ID and a ε -useful pirate decoder $\mathbb{D}$, conduct the following steps.

- a. Set $\text{ctr} \leftarrow 0$ and repeat the next steps $L = 16\lambda/\varepsilon$ times:
 1. Choose $s, s' \xleftarrow{\$} \mathbb{Z}_p^*$ such that $s \neq s'$ and set $C_1 = (g_1 \cdot g^{-\text{ID}})^s$ and $C_2 = e(g, h)^{s'}$.
 2. Compute $C_3 = m \cdot e(C_1, d) \cdot C_2^{t_{\text{ID}}}$ for a random message $m \in \mathbb{G}_T$.
 3. Feed the decryption device $\mathbb{D}$ with (C_1, C_2, C_3) . If $\mathbb{D}$ outputs $m' \in \mathbb{G}_T$ such that $m' = m$, increment ctr .
- b. If $\text{ctr} = 0$, incriminate the PKG. Otherwise, incriminate the user.

The IND-ID-CPA security of the scheme can be simply reduced to that of Gentry's IBE as shown in the proof of the next theorem.

Theorem 6. *Any IND-ID-CPA adversary against the above A-IBE implies an IND-ID-CPA attacker against Gentry's IBE.*

Proof. Let us assume an IND-ID-CPA adversary $\mathcal{A}$ in the game described by definition 2. We show that $\mathcal{A}$ gives rise to an IND-ID-CPA adversary $\mathcal{B}$ against Gentry's IBE.

Our adversary $\mathcal{B}$ receives a master public key $\text{mpk} = (g, g_1, h)$ from her challenger. When $\mathcal{A}$ makes a key generation request for an identity ID , $\mathcal{B}$ queries her own challenger to extract a private key $d_{\text{ID}} = (d, t_{\text{ID}}) = ((h \cdot g^{-t_{\text{ID}}})^{1/(\alpha - \text{ID})}, t_{\text{ID}})$ and starts executing the key generation protocol with in interaction with $\mathcal{A}$. The latter first supplies a commitment $R = g^{-t_0} \cdot (g_1 \cdot g^{-\text{ID}})^\theta$ and an interactive WI proof of knowledge of the pair (t_0, θ) . Using the knowledge extractor of the proof of knowledge, $\mathcal{B}$ extracts (t_0, θ) by rewinding $\mathcal{A}$ and returns $d_{\text{ID}} = (d', t'_{\text{ID}})$, where $t'_{\text{ID}} = t_{\text{ID}} - t_0$ and $d' = d_{\text{ID}} \cdot g^\theta$.

In the challenge phase, $\mathcal{A}$ chooses a target identity ID^* and messages (m_0, m_1) , which $\mathcal{B}$ forwards to her own challenger. The latter provides $\mathcal{B}$ with a challenge ciphertext (C_1, C_2, C_3) which is relayed to $\mathcal{A}$. After a second series of key generation queries, $\mathcal{A}$ outputs a bit $d \in \{0, 1\}$, which is also $\mathcal{B}$'s output. It is easy to see that, if $\mathcal{A}$ is successful, so is $\mathcal{B}$. $\square$

We now turn to prove the weak black-box traceability property.

Lemma 3. *In the Adaptive-ID ComputeNewKey game and for a ε -useful device $\mathbb{D}$, the probability that an iteration of the tracing algorithm increases ctr is at least $p_1 \geq \varepsilon - \text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{q\text{-ADBDHE}}(\lambda)$, where q is the number of key generation queries.*

Proof. The proof is very similar to the proof of IND-ID-CPA security in [21]. For the sake of contradiction, let us assume that, in an iteration of the tracing procedure, the probability p_1 that $\mathbb{D}$ returns the message chosen by the tracer is significantly smaller than ε . Then, we can construct a distinguisher $\mathcal{B}$ for the q -ADBDHE assumption.

The distinguisher $\mathcal{B}$ takes as input a tuple $(g, g^\alpha, \dots, g^{(\alpha^q)}, h, h^{(\alpha^{q+2})}, T)$ and aims at deciding if $T = e(g, h)^{(\alpha^{q+1})}$. It generates the master public key in such a way that $h = g^{f(\alpha)}$, for some random polynomial $f(X) \in \mathbb{Z}_p[X]$ of degree q . At each key generation query, $\mathcal{B}$ first computes a valid private key $d_{\text{ID}} = (d, t_{\text{ID}})$ for the identity ID , by setting $t_{\text{ID}} = f(\text{ID})$ as in the proof of theorem 1 in [21]. Then, in the interactive key generation protocol, $\mathcal{A}$ sends a commitment $R = g^{-t_0} \cdot (g_1 \cdot g^{-\text{ID}})^\theta$ and proves knowledge of the pair (t_0, θ) , which $\mathcal{B}$ extracts by rewinding $\mathcal{A}$ as in the proof of theorem 6. As in the latter, $\mathcal{B}$ replies with a well-distributed pair $d'_{\text{ID}} = (d', t'_{\text{ID}})$, where $t'_{\text{ID}} = t_{\text{ID}} - t_0$ and $d' = d \cdot g^\theta$.

The game ends with $\mathcal{A}$ outputting an identity ID^* , a private key $d_{\text{ID}^*} = (d^*, t_{\text{ID}^*}^*)$ and a ε -useful device. In the tracing stage, $\mathcal{B}$ first expands the monic polynomial $F(X) = (X^{q+2} - \text{ID}^{*q+2}) / (X - \text{ID}^*) = X^{q+1} + F_q X^q + \dots + F_1 X + F_0$. Then, $\mathcal{B}$ chooses a plaintext $m \xleftarrow{\$} \mathbb{G}_T$ and computes $C = (C_1, C_2, C_3)$ as

$$C_1 = \frac{h^{(\alpha^{q+2})}}{h^{(\text{ID}^{*q+2})}} \quad C_2 = T \cdot e\left(h, \prod_{j=0}^q (g^{(\alpha^j) F_j})\right) \quad C_3 = m \cdot e(C_1, d^*) \cdot C_2^{t_{\text{ID}^*}^*}.$$

If $\mathbb{D}$ returns the correct plaintext m , the distinguisher $\mathcal{B}$ halts and return 1. As in [21], (C_1, C_2, C_3) is a well-formed ciphertext with the encryption exponent

$s = \log_g(h)F(\alpha)$ if $T = e(g, h)^{(\alpha^{q+1})}$. In this case, $\mathcal{B}$ returns 1 with probability ε since $\mathbb{D}$ is a ε -useful device. By assumption, the probability that $\mathcal{B}$ returns 1 when T is random is significantly smaller than ε . Therefore, $\mathcal{B}$ has non-negligible advantage as a distinguisher against the q -ADBDHE assumption. $\square$

Theorem 7. *In the adaptive-ID ComputeNewKey game, any PPT adversary has negligible advantage assuming that the ADBDHE assumption holds.*

Proof. The proof is completely analogous to that of theorem 4. $\square$

The weak black-box security against dishonest PKGs follows from the information theoretic secrecy of the user's private key element t_{ID} upon termination of the key generation protocol.

Theorem 8. *In the information theoretic sense, no adversary has an advantage in the FindKey-CPA game.*

To secure the scheme against chosen-ciphertext attacks, we cannot use hash proof systems as suggested in [21, 29]. This technique would indeed cause the decryption algorithm to reject all invalid ciphertexts with high probability, which would not be compatible with our weak black-box tracing mechanism.

Fortunately, CCA2-security can be acquired by applying the Canetti-Halevi-Katz transformation to a two-receiver variant of the Gentry-Waters identity-based broadcast encryption (IBBE) scheme [22]: one of the two receivers' identities is set to be the verification key of a strongly unforgeable one-time signature and the matching private key is used to sign the whole ciphertext.

Our tracing algorithm can be combined with the latter approach since, in the Gentry-Waters IBBE [22], private keys have the same shape as in Gentry's IBE and one of the ciphertext components lives in the group $\mathbb{G}_T$. As already mentioned, the CHK technique does not affect traceability as, upon decryption, ill-formed ciphertexts only get rejected when the one-time signature verification fails. The computational/bandwidth cost of the resulting system exceeds that of the above A-IBE construction only by a small factor.

6 Extension to Identity-Based Broadcast Encryption

As already stressed in [24, 25], reducing the required amount of trust in PKGs is an equally important problem in IBE schemes and their extensions such as attributed-based encryption or identity-based broadcast encryption (IBBE).

In this section, we thus show how the underlying idea of previous schemes can be applied to one of the most efficient IBBE realizations to date.

6.1 The Boneh-Hamburg IBBE

An identity-based broadcast encryption scheme, as formalized in [2], can be seen as an IBE where ciphertexts can be decrypted by more than one receiver. Syntactically, it consists of four algorithms:

- **Setup**: given a security parameter and a bound N on the number of receivers per ciphertext, this algorithm outputs a master key pair (mpk, msk) .
- **KeyGen**: is used by the PKG to derive a private key K_{ID} for an identity ID .
- **Encrypt**: takes as input a plaintext m , a master public key mpk and a set $S = \{\text{ID}_1, \dots, \text{ID}_n\}$ of receivers' identities, where $n \leq N$. It outputs a ciphertext C .
- **Decrypt**: takes as input the master public key mpk , a ciphertext C , a set of receivers $S = \{\text{ID}_1, \dots, \text{ID}_n\}$ and a private key d_{ID} corresponding to some identity $\text{ID} \in S$. It outputs a plaintext m or $\perp$.

In [10], Boneh and Hamburg showed how to turn the Boneh-Boyen-Goh hierarchical IBE [7] into an efficient IBBE system with constant-size ciphertexts and linear-size private keys in the bound N on the number of receivers per ciphertext. Their construction was shown to derive from a more general primitive termed “spatial encryption”. Its security (in the selective-ID sense) was established under the following assumption introduced in [7].

Definition 5. Let $(\mathbb{G}, \mathbb{G}_T)$ be bilinear groups of order p and $g \in \mathbb{G}$. The ℓ -**Decision Bilinear Diffie-Hellman Exponent** (ℓ -DBDHE) problem is, given $(g, g^\alpha, g^{(\alpha^2)}, \dots, g^{(\alpha^\ell)}, g^{(\alpha^{\ell+2})}, \dots, g^{(\alpha^{2\ell})}, h, T) \in \mathbb{G}^{2\ell+1} \times \mathbb{G}_T$ for random $\alpha \xleftarrow{\$} \mathbb{Z}_p^*$ and $h \xleftarrow{\$} \mathbb{G}$, to decide whether $T = e(g, h)^{(\alpha^{\ell+1})}$. The advantage $\text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{\ell\text{-DBDHE}}(\lambda)$ of a distinguisher $\mathcal{B}$ is defined in the usual way.

In the following, we use the same notations as in [10] and, for any vector $\mathbf{a} = (a_0, \dots, a_N) \in \mathbb{Z}_p^{N+1}$, $g^{\mathbf{a}}$ stands for the vector $(g^{a_0}, \dots, g^{a_N}) \in \mathbb{G}^{N+1}$. The description of the Boneh-Hamburg IBBE scheme is as follows.

Setup (λ, N) : given a security parameter $\lambda \in \mathbb{N}$ and the maximal number of receivers $N \in \mathbb{N}$ per ciphertext, choose bilinear groups $(\mathbb{G}, \mathbb{G}_T)$ of prime order $p > 2^\lambda$ and a generator $g \xleftarrow{\$} \mathbb{G}$. Choose $z \xleftarrow{\$} \mathbb{G}$ as well a $(N+1)$ -vector $\mathbf{h} = (h_0, h_1, \dots, h_N) \xleftarrow{\$} \mathbb{G}^{N+1}$ of random generators so that $h_i = g^{a_i}$ for $i = 0, \dots, N$ with a randomly chosen $\mathbf{a} = (a_0, \dots, a_N) \xleftarrow{\$} \mathbb{Z}_p^{N+1}$. Finally, pick $\alpha \xleftarrow{\$} \mathbb{Z}_p^*$, $g_2 \xleftarrow{\$} \mathbb{G}$ and compute $g_1 = g^\alpha$. The master public key is $\text{mpk} = (g, g_1 = g^\alpha, g_2, z, \mathbf{h} = g^{\mathbf{a}})$ while the master secret key is $\text{msk} = (\mathbf{a}, \alpha)$.

Keygen (msk, ID) : to generate a private key for an identity ID , choose a random $r \xleftarrow{\$} \mathbb{Z}_p^*$ and compute

$$\begin{aligned} K_{\text{ID}} &= (K_1, K_2, T_0, \dots, T_{N-1}) \\ &= (g_2^\alpha \cdot z^r, g^r, h_1^r \cdot h_0^{-\text{ID} \cdot r}, h_2^r \cdot h_1^{-\text{ID} \cdot r}, \dots, h_N^r \cdot h_{N-1}^{-\text{ID} \cdot r}) \end{aligned}$$

for which the “delegation component” $(T_0, \dots, T_{N-1}) \in \mathbb{G}^N$ can be expressed as $g^{r \cdot M_1^t \cdot \mathbf{a}}$, for some matrix $M_1 \in \mathbb{Z}_p^{(N+1) \times N}$, which will be defined below.

Encrypt (mpk, S, m) : to encrypt $m \in \mathbb{G}_T$ for the receiver set $S = \{\text{ID}_1, \dots, \text{ID}_n\}$, where $n \leq N$,

1. Expand the polynomial

$$P(X) = \prod_{i \in S} (X - \text{ID}_i) = \rho_n X^n + \rho_{n-1} X^{n-1} + \dots + \rho_1 X + \rho_0. \quad (11)$$

2. Pick $s \xleftarrow{\$} \mathbb{Z}_p^*$ and compute

$$C = (C_0, C_1, C_2) = \left(m \cdot e(g_1, g_2)^s, g^s, (z \cdot h_0^{\rho_0} \cdot h_1^{\rho_1} \dots h_n^{\rho_n})^s \right).$$

Decrypt(mpk, K_{ID} , C , S): parse S as $\{\text{ID}_1, \dots, \text{ID}_n\}$, C as (C_0, C_1, C_2) and K_{ID} as

$$K_{\text{ID}} = (K_1, K_2, T_0, \dots, T_{N-1}) \in \mathbb{G}^{N+2}.$$

1. Expand the polynomial

$$P_{\text{ID}}(X) = \prod_{\text{ID}_j \in S \setminus \{\text{ID}\}} (X - \text{ID}_j) = y_{n-1}^{(\text{ID})} X^{n-1} + y_{n-2}^{(\text{ID})} X^{n-2} + \dots + y_1^{(\text{ID})} X + y_0^{(\text{ID})}$$

and use its coefficients to compute

$$(D_{\text{ID}}, d_{\text{ID}}) = (K_1 \cdot T_0^{y_0^{(\text{ID})}} \cdot T_1^{y_1^{(\text{ID})}} \dots T_{n-1}^{y_{n-1}^{(\text{ID})}}, K_2) \quad (12)$$

$$= (g_2^\alpha \cdot (z \cdot h_0^{\rho_0} \cdot h_1^{\rho_1} \dots h_n^{\rho_n})^r, g^r) \quad (13)$$

where $\rho_0, \dots, \rho_n$ are the coefficients of $P(X)$ (calculated as per (11)).

2. Recover the plaintext as

$$m = C_0 \cdot e(C_1, D_{\text{ID}})^{-1} \cdot e(C_2, d_{\text{ID}}). \quad (14)$$

To see why step 1 of the decryption algorithm works, one observes that, for any polynomials $(X - \text{ID})$ and $P_{\text{ID}}(X) = y_{n-1}^{(\text{ID})} X^{n-1} + y_{n-2}^{(\text{ID})} X^{n-2} + \dots + y_1^{(\text{ID})} X + y_0^{(\text{ID})}$, the coefficients of $P(X) = (X - \text{ID})P_{\text{ID}}(X) = \rho_n X^n + \dots + \rho_1 X + \rho_0$ are given by

$$\rho = \begin{pmatrix} \rho_0 \\ \rho_1 \\ \rho_2 \\ \vdots \\ \rho_n \end{pmatrix} = M_1 \cdot \mathbf{y} = \begin{pmatrix} -\text{ID} & & & & \\ 1 & -\text{ID} & & & \\ & 1 & -\text{ID} & & \\ & & \ddots & \ddots & \\ & & & 1 & -\text{ID} \\ & & & & 1 \end{pmatrix} \cdot \begin{pmatrix} y_0^{(\text{ID})} \\ y_1^{(\text{ID})} \\ \vdots \\ y_{n-1}^{(\text{ID})} \end{pmatrix},$$

where $M_1 \in \mathbb{Z}_p^{(n+1) \times n}$. Since the latter matrix is such that

$$M_1^t \cdot \mathbf{a}|_{n+1} = M_1^t \cdot \begin{pmatrix} a_0 \\ a_1 \\ \vdots \\ a_n \end{pmatrix} = \begin{pmatrix} a_1 - \text{ID} \cdot a_0 \\ a_2 - \text{ID} \cdot a_1 \\ \vdots \\ a_n - \text{ID} \cdot a_{n-1} \end{pmatrix},$$

for each private key K_{ID} , the first n delegation components satisfy

$$(T_0, \dots, T_{n-1}) = (h_1^r \cdot h_0^{-\text{ID} \cdot r}, h_2^r \cdot h_1^{-\text{ID} \cdot r}, \dots, h_n^r \cdot h_{n-1}^{-\text{ID} \cdot r}) = g^{r M_1^t \cdot \mathbf{a}}.$$

Therefore, since $\rho = M_1 \cdot \mathbf{y}$, we have

$$(z \cdot \prod_{k=0}^n h_k^{\rho_k})^r = z^r \cdot g^{r \cdot \rho^t \cdot \mathbf{a}} = z^r \cdot g^{r \mathbf{y}^t \cdot M_1^t \cdot \mathbf{a}} = z^r \cdot T_0^{y_0^{(\text{ID})}} \dots T_{n-1}^{y_{n-1}^{(\text{ID})}}$$

which explains the transition between relations (12) and (13). To explain the second step of the decryption algorithm, we note that, for each $\text{ID} \in S$, the pair $(D_{\text{ID}}, d_{\text{ID}})$ satisfies

$$e(D_{\text{ID}}, g) = e(g_1, g_2) \cdot e(z \cdot h_0^{\rho_0} \cdot h_1^{\rho_1} \dots h_n^{\rho_n}, d_{\text{ID}}) \quad (15)$$

By raising both members of (15) to the power $s \in \mathbb{Z}_p^*$, where s is the random encryption exponent, we see why m can be recovered as per (14).

The security of this scheme was proved [10] under the $(N + 1)$ -DBDHE assumption in the selective-ID model. In the context of IBBE schemes, the IND-sID-CPA model was formalized in [2]. It requires the adversary to choose upfront (*i.e.*, before seeing mpk) the set $S^* = \{\text{ID}_1^*, \dots, \text{ID}_{n^*}^*\}$ of identities under which the challenge ciphertext C^* will be generated. The adversary is then allowed to query private keys for identities $\text{ID}_i \notin S^*$ and eventually aims at guessing which one out of two messages of her choice was encrypted in the generation of C^* .

6.2 A weak Black-Box Accountable Authority IBBE

The idea of the scheme in section 3 applies to construct an IBBE scheme with short ciphertexts and accountable authorities. The syntax of accountable authority IBBE (A-IBBE) schemes extends that of IBBE systems in the same way as the A-IBE primitive extends IBE. The resulting construction goes as follows.

Setup (λ, N) : is as in the Boneh-Hamburg IBBE but the algorithm chooses an additional random group element g_3 . The master public key thus consists of $\text{mpk} = (g, g_1 = g^\alpha, g_2, g_3, z, \mathbf{h} = g^{\mathbf{a}})$ while the master secret is $\text{msk} = (\mathbf{a}, \alpha)$.

Keygen $^{(\text{PKG}, \text{U})}$: the two parties conduct the following interactive steps.

1. U picks $t_0, \theta \xleftarrow{\$} \mathbb{Z}_p^*$ and sends a commitment $R = g_2^{t_0} \cdot g^\theta$ to the PKG and provides an interactive WI proof of knowledge of (t_0, θ) .
2. The PKG outputs $\perp$ if the proof of knowledge is invalid. Otherwise, it picks $r, t_1 \xleftarrow{\$} \mathbb{Z}_p^*$ and returns

$$\begin{aligned} K'_{\text{ID}} &= (K'_1, K'_2, T'_0, \dots, T'_{N-1}, t'_{\text{ID}}) \\ &= ((g_2^{t_1} \cdot R \cdot g_3)^\alpha \cdot z^r, g^r, h_1^r \cdot h_0^{-\text{ID} \cdot r}, h_2^r \cdot h_1^{-\text{ID} \cdot r}, \dots, h_N^r \cdot h_{N-1}^{-\text{ID} \cdot r}, t_1) \end{aligned}$$

3. $\mathbf{U}$ picks $r' \xleftarrow{\$} \mathbb{Z}_p^*$ and computes $K_{\text{ID}} = (K_1, K_2, T_0, \dots, T_{N-1}, t_{\text{ID}})$, where $K_1 = (K'_1/g_1^\theta) \cdot z^{r'}$, $K_2 = K'_2 \cdot g^{r'}$, $T_i = T'_i \cdot (h_{i+1} \cdot h_i^{-\text{ID}})^{r'}$ for indices $i = 0, \dots, N-1$ and $t'_{\text{ID}} + t_0$, so that

$$\begin{aligned} K_{\text{ID}} &= (K_1, K_2, T_0, \dots, T_{N-1}, t_{\text{ID}}) \\ &= \left((g_2^{t_0+t_1} \cdot g_3)^\alpha \cdot z^{r''}, g^{r''}, h_1^{r''} \cdot h_0^{-\text{ID} \cdot r''}, \dots, h_N^{r''} \cdot h_{N-1}^{-\text{ID} \cdot r''}, t_0 + t_1 \right), \end{aligned}$$

where $r'' = r + r'$. Then, $\mathbf{U}$ checks whether d_{ID} satisfies the relation

$$e(K_1, g) = e(g_1, g_2)^{t_{\text{ID}}} \cdot e(g_1, g_3) \cdot e(z, K_2),$$

and $e(g, T_i) = e(K_2, h_{i+1} \cdot h_i^{-\text{ID}})$ for each $i \in \{0, \dots, N-1\}$.

Encrypt(mpk, S, m): to encrypt $m \in \mathbb{G}_T$ for the receiver set $S = \{\text{ID}_1, \dots, \text{ID}_n\}$, where $n \leq N$,

1. Expand $P(X) \in \mathbb{Z}_p[X]$ as

$$P(X) = \prod_{i \in S} (X - \text{ID}_i) = \rho_n X^n + \rho_{n-1} X^{n-1} + \dots + \rho_1 X + \rho_0.$$

2. Choose $s \xleftarrow{\$} \mathbb{Z}_p^*$ and compute

$$\begin{aligned} C &= (C_0, C_1, C_2, C_3) \\ &= \left(m \cdot e(g_1, g_3)^s, g^s, (z \cdot h_0^{\rho_0} \cdot h_1^{\rho_1} \dots h_n^{\rho_n})^s, e(g_1, g_2)^s \right). \end{aligned}$$

Decrypt(mpk, K_{ID}, C, S): parse C as (C_0, C_1, C_2, C_3) and K_{ID} as

$$K_{\text{ID}} = (K_1, K_2, T_0, \dots, T_{N-1}, t_{\text{ID}}) \in \mathbb{G}^{N+2} \times \mathbb{Z}_p.$$

1. Expand $P_{\text{ID}}(X) \in \mathbb{Z}_p[X]$ as

$$P_{\text{ID}}(X) = \prod_{\text{ID}_j \in S \setminus \{\text{ID}\}} (X - \text{ID}_j) = y_{n-1}^{(\text{ID})} X^{n-1} + y_{n-2}^{(\text{ID})} X^{n-2} + \dots + y_1^{(\text{ID})} X + y_0^{(\text{ID})}$$

and compute the decryption key

$$\begin{aligned} (D_{\text{ID}}, d_{\text{ID}}, t_{\text{ID}}) &= (K_1 \cdot T_0^{y_0^{(\text{ID})}} \cdot T_1^{y_1^{(\text{ID})}} \dots T_{n-1}^{y_{n-1}^{(\text{ID})}}, K_2, t_{\text{ID}}) \\ &= \left((g_2^{t_{\text{ID}}} \cdot g_3)^\alpha \cdot (z \cdot h_0^{\rho_0} \cdot h_1^{\rho_1} \dots h_n^{\rho_n})^r, g^r, t_{\text{ID}} \right). \end{aligned}$$

2. Recover the plaintext as

$$m = C_0 \cdot e(C_1, D_{\text{ID}})^{-1} \cdot e(C_2, d_{\text{ID}}) \cdot C_3^{t_{\text{ID}}}.$$

Trace ^{$\mathbb{D}$} ($\text{mpk}, K_{\text{ID}}, \varepsilon$): given a valid private key K_{ID} for the identity ID and a ε -useful decoder $\mathbb{D}$, the tracing algorithm proceeds in a similar fashion to previous schemes, by feeding $\mathbb{D}$ with ciphertexts $C = (C_0, C_1, C_2, C_3)$ and the receiver set S . In the generation of C , C_1 and C_2 are calculated as specified by the encryption algorithm. On the other hand, C_3 is chosen as a random element of $\mathbb{G}_T$ and C_0 is obtained by applying the decryption algorithm to S and (C_1, C_2, C_3) .

Correctness is implied the fact that the decryption key $(D_{\text{ID}}, d_{\text{ID}}, t_{\text{ID}})$ satisfies the relation $e(D_{\text{ID}}, g) = e(g_1, g_2)^{t_{\text{ID}}} \cdot e(g_1, g_3) \cdot e(z \cdot \prod_{i=0}^n h_i^{\rho_i}, d_{\text{ID}})$ and raising both members to the power s as in previous schemes.

To avoid repeating the work of Boneh and Hamburg, we prove the security properties of the above A-IBBE system by reducing them to the IND-sID-CPA security of the underlying IBBE.

Theorem 9. *The A-IBBE scheme is secure under the $(N+1)$ -DBDHE assumption. More precisely, any IND-sID-CPA adversary against it implies an equally successful IND-sID-CPA attacker against the Boneh-Hamburg IBBE.*

Proof. We show that an IND-sID-CPA adversary $\mathcal{A}$ against the A-IBBE scheme gives rise to a “real-or-random” IND-sID-CPA adversary $\mathcal{B}$ (i.e., in which the adversary $\mathcal{A}$ outputs a single message m and has to decide whether the challenge ciphertext C^* encrypts m or a random message) against the Boneh-Hamburg IBBE. Hence, the security of the latter implies the security of our scheme.

When $\mathcal{A}$ chooses her set of target identities $S^* = \{\text{ID}_1^*, \dots, \text{ID}_{n^*}^*\}$, with $n^* \leq N$, our adversary $\mathcal{B}$ forwards S^* to her own challenger and receives a master public key $\text{mpk}^{\text{BH}} = (g, g_1 = g^\alpha, g_2, z, \mathbf{h} = g^{\mathbf{a}})$. Then, $\mathcal{B}$ picks $t^*, \beta \xleftarrow{\$} \mathbb{Z}_p^*$, computes $g_3 = g_2^{-t^*} g^\beta$ and provides $\mathcal{A}$ with $\text{mpk} = (g, g_1, g_2, g_3, z, \mathbf{h})$.

At any time, $\mathcal{A}$ may request an execution of the key generation protocol for an arbitrary identity $\text{ID} \notin S^*$. At the beginning of each such protocol, $\mathcal{A}$ sends a commitment $R = g_2^{t_0} \cdot g^\theta$ and interactively proves knowledge of (t_0, θ) , which $\mathcal{B}$ extracts by rewinding $\mathcal{A}$. Then, $\mathcal{B}$ chooses $t_1 \xleftarrow{\$} \mathbb{Z}_p^*$, sets $t = t_0 + t_1$ and queries her own IND-sID-CPA challenger to obtain a private key

$$\tilde{K}_{\text{ID}} = (\tilde{K}_1, \tilde{K}_2, \tilde{T}_0, \dots, \tilde{T}_{N-1}) = (g_2^\alpha \cdot z^r, g^r, h_1^r \cdot h_0^{-\text{ID} \cdot r}, h_2^r \cdot h_1^{-\text{ID} \cdot r}, \dots, h_N^r \cdot h_{N-1}^{-\text{ID} \cdot r})$$

for the identity ID chosen by $\mathcal{A}$. The latter is turned into an A-IBBE private key and re-randomized by setting

$$K_{\text{ID}} = (K_1, K_2, T_0, \dots, T_{N-1}) = (g_1^\beta \cdot \tilde{K}_1^{(t-t^*)} \cdot z^{r'}, \tilde{K}_2^{(t-t^*)} \cdot g^{r'}, \tilde{T}_0^{(t-t^*)} \cdot (h_1 \cdot h_0^{-\text{ID}})^{r'}, \dots, \tilde{T}_{n-1}^{(t-t^*)} \cdot (h_N \cdot h_{N-1}^{-\text{ID}})^{r'}),$$

where $r' \xleftarrow{\$} \mathbb{Z}_p^*$. The new key K_{ID} is easily seen to have the same distribution as those obtained in step 3 of the key generation protocol. Finally, $\mathcal{A}$ obtains the “blinded key” $K'_{\text{ID}} = (K'_1, K'_2, T'_0, \dots, T'_{N-1})$, where $K'_1 = K_1 \cdot g_1^\theta$.

In the challenge phase, $\mathcal{A}$ chooses a pair of target messages (m_0, m_1) . The

adversary $\mathcal{B}$ chooses a random plaintext $m^* \xleftarrow{\$} \mathbb{G}_T$, which she sends to her own “real-or-random” challenger. The latter replies with a challenge ciphertext

$$C^* = (C_0, C_1, C_2) = \left(m \cdot e(g_1, g_2)^{s^*}, g^{s^*}, (z \cdot h_0^{\rho_0} \cdot h_1^{\rho_1} \cdots h_n^{\rho_n})^{s^*} \right).$$

for the receiver set $S^* = \{\text{ID}_1^*, \dots, \text{ID}_n^*\}$, where m is either m^* or a random element of $\mathbb{G}_T$. The adversary $\mathcal{B}$ picks a random bit $d \xleftarrow{\$} \{0, 1\}$ and computes $C' = (C'_0, C_1, C_2, C_0/m^*)$ where $C'_0 = m_d \cdot (C_0/m^*)^{-t^*} \cdot e(g_1, C_1)^\beta$ and C' is relayed to $\mathcal{A}$ as a challenge ciphertext. After a second series of key generation queries, $\mathcal{A}$ outputs a bit $d' \in \{0, 1\}$, and $\mathcal{B}$ outputs “real” if $d' = d$ and “random” otherwise. It is easy to see that, if C^* encrypts a random plaintext, then C_0/m^* can be expressed as $C_0/m^* = e(g_1, g_2)^{s^* - s'}$, where $s^* = \log_g(C_1)$ and for some $s' \neq 0$. In this case, we obtain that $C'_0 = m_d \cdot e(g_1, g_3)^{s^*} \cdot e(g_1, g_2)^{s' t^*}$ statistically hides m_d (and thus $\Pr[d' = d] = 1/2$) since $\mathcal{A}$ has no information on t^* . In contrast, if C^* encrypts m^* , then C' is a valid encryption of m_d for the A-IBBE scheme, so that $\Pr[d' = d] = 1/2 + \text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{\text{BH-IND-sID-CPA}}(\lambda)$, where the latter advantage function denotes the maximal “real-or-random” advantage of any IND-sID-CPA adversary against the Boneh-Hamburg IBBE. It comes that $\mathcal{B}$ ’s advantage in the real-or-random game is exactly $\text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{\text{BH-IND-sID-CPA}}(\lambda)$. $\square$

Lemma 4. *In the selective-ID ComputeNewKey game and for a ε -useful decryption device $\mathbb{D}$, the probability that an iteration of the tracing procedure increases ctr is at least $p_1 \geq \varepsilon - \text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{(N+1)\text{-DBDHE}}(\lambda)$.*

Proof. Let us assume that, at the end of the selective-ID ComputeNewKey game, the dishonest user $\mathcal{A}$ outputs a device $\mathbb{D}$ for which a given iteration of the tracing procedure increments ctr with a probability p_1 , which is significantly smaller than ε . Then, we show how to obtain an IND-sID-CPA adversary $\mathcal{B}$ against the Boneh-Hamburg IBBE.

The adversary $\mathcal{B}$ plays the IND-sID-CPA game against a challenger $\mathcal{C}^{\text{BH}}$ and plays $\mathcal{A}$ ’s challenger in the selective-ID ComputeNewKey game. At the outset of the latter, $\mathcal{A}$ chooses a target identity ID^* and $\mathcal{B}$ chooses her set of target identities as $S^* = \{\text{ID}^*\}$. When seeing the description of S^* , the IBBE challenger $\mathcal{C}^{\text{BH}}$ generates a master public key $\text{mpk}^{\text{BH}} = (g, g_1, g_2, z, \mathbf{h})$. Then, $\mathcal{B}$ chooses $t^*, \beta \xleftarrow{\$} \mathbb{Z}_p^*$ and sets $g_3 = g_2^{-t^*} \cdot g^\beta$. The master public key of the A-IBBE system is defined as $\text{mpk} = (g, g_1, g_2, g_3, z, \mathbf{h})$ and given to $\mathcal{A}$.

Then, $\mathcal{A}$ starts making a number of key generation queries. For each key generation query involving an identity $\text{ID} \neq \text{ID}^*$, $\mathcal{B}$ proceeds by invoking her own challenger $\mathcal{C}^{\text{BH}}$, exactly as in the proof of theorem 9. When $\mathcal{A}$ queries a private key K_{ID^*} for the target identity ID^* , $\mathcal{B}$ first rewinds the proof of knowledge so as to extract the pair (t_0, θ) such that $R = g_2^{t_0} \cdot g^\theta$ in the commitment. Then, it sets $t_1 = t^* - t_0$ (in such a way that $t = t_0 + t_1 = t^*$). In this case, $\mathcal{B}$ can compute an A-IBBE private key K_{ID^*} on her own (without having to query $\mathcal{C}^{\text{BH}}$) as

$$(K_1, K_2, T_0, \dots, T_{N-1}, t_{\text{ID}^*}) = (g_1^\beta \cdot z^r, g^r, (h_1 \cdot h_0^{-\text{ID}^*})^r, \dots, (h_N \cdot h_{N-1}^{-\text{ID}^*})^r, t^*),$$

which is well-formed since $g_2^{t^*} \cdot g_3 = g^\beta$. Finally, $\mathcal{B}$ returns the “blinded key” $K'_{ID^*} = (g_1^\theta \cdot K_1, K_2, T_0, \dots, T_{N-1}, t_1)$ to $\mathcal{A}$.

At the end of the game, $\mathcal{A}$ outputs a private key K_{ID^*} and a ε -useful device for the identity ID^* . In the tracing stage, $\mathcal{B}$ sends a random plaintext $m^* \xleftarrow{\$} \mathbb{G}_T$ to $\mathcal{C}^{BH}$ who replies with a challenge (C_0^*, C_1^*, C_2^*) , where $C_0^* = m^* \cdot e(g_1, g_2)^{s^*}$ and $C_1 = g^{s^*}$ if $\mathcal{C}^{BH}$ is playing the “real” game. On the other hand, if $\mathcal{C}^{BH}$ decides to play the “random” game, C_0^* is random in $\mathbb{G}_T$. To construct a ciphertext for the A-IBBE scheme, $\mathcal{B}$ sets $C_3 = C_0^*/m^*$ (which equals $e(g_1, g_2)^{s^*}$ in the “real” game and $e(g_1, g_2)^{s'}$, with $s' \neq s^*$ in the “random” game), $C_1 = C_1^*$ and $C_2 = C_2^*$. To compute C_0 , $\mathcal{B}$ chooses $m \xleftarrow{\$} \mathbb{G}_T$ and calculates

$$C_0 = m \cdot e(C_1, D_{ID^*}) \cdot e(C_2, d_{ID^*})^{-1} \cdot C_3^{-t^*}, \quad (16)$$

where $(D_{ID^*}, d_{ID^*}, t^*)$ is the decryption key for the identity ID^* and the receiver set S^* , which is obtained from K_{ID^*} .

If $\mathbb{D}$ returns the correct plaintext m , the distinguisher $\mathcal{B}$ halts and outputs “real” (meaning that $\mathcal{C}^{BH}$ is playing the “real” game). Otherwise, $\mathcal{B}$ outputs “random”. In the former case, (C_0, C_1, C_2, C_3) is a valid ciphertext for the receiver set $S^* = \{ID^*\}$ and $\mathcal{B}$ returns 1 with probability ε since $\mathbb{D}$ is a ε -useful device. If $\mathcal{C}^{BH}$ plays the random game, $\log_g(C_1) \neq \log_{e(g_1, g_2)}(C_3)$ and (C_0, C_1, C_2, C_3) has the distribution of a ciphertext generated in iterations of the tracing stage. In this case, the probability that $\mathbb{D}$ returns the plaintext m is p_1 . By the definition of IND-sID-CPA security of the IBBE scheme, we must have $\varepsilon - p_1 \leq \text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{\text{BH-IND-sID-CPA}}(\lambda)$. Since the result of [10] implies that $\text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{\text{BH-IND-sID-CPA}}(\lambda) \leq \text{Adv}_{\mathbb{G}, \mathbb{G}_T}^{(N+1)\text{-DBDHE}}(\lambda)$, the claimed result follows. $\square$

Theorem 10. *In the selective-ID ComputeNewKey game, any PPT adversary has negligible advantage assuming that the $(N + 1)$ -DBDHE assumption holds.*

Proof. Again, the proof is similar to the one of theorem 4 and is omitted. $\square$

As in previous schemes, as long as pirate devices are stateless, no dishonest PKG can create one that gets the tracing procedure to accuse the user and the result holds unconditionally.

Theorem 11. *In the information theoretic sense, no adversary has an advantage in the FindKey-CPA game.*

We remark that it is possible to re-write the description of our scheme of section 3 in such a way that its security properties can be reduced to the security of the first Boneh-Boyen IBE [5] (in the same way as we reduced the security of our A-IBBE to the security of the underlying IBBE). However, giving a proof from scratch allowed us to avoid rewinding as much as possible in section 3. It would be interesting to see if, in our A-IBBE, the number of rewinds can also be minimized by giving direct proofs under the $(N + 1)$ -DBDHE assumption for theorem 9 and lemma 4.

It is also noteworthy that other IBE-related primitives can be made accountable using the same technique. Due to their algebraic similarities with the “commutative blinding” IBE family, the “large-universe” attribute-based encryption

schemes described in [35, 26] can easily be tweaked to support accountability in the weak black-box model.

7 Conclusion

We described the first A-IBE system allowing for weak black-box traceability while retaining short ciphertexts and private keys. We also suggested a white-box variant that dwells secure against dishonest PKGs equipped with a decryption oracle. In the black-box setting, it remains an open problem to achieve the latter property without significantly degrading the efficiency.

In the setting of hierarchical IBE schemes, it would also be desirable to see how the problem can be addressed. When a pirate decoder is found to decrypt ciphertexts intended for a node, one should be able to determine which ancestor(s) of that node should be blamed.

References

1. M. Abdalla, A. Dent, J. Malone-Lee, G. Neven, D.-H. Phan, N. Smart. Identity-Based Traitor Tracing. In *PKC'07, LNCS* 4450, pp. 361–376, 2007.
2. M. Abdalla, E. Kiltz, G. Neven. Generalized Key Delegation for Hierarchical Identity-Based Encryption. In *ESORICS'07, LNCS* 4734, pp. 139–154. Springer, 2007.
3. S. Al-Riyami, K. Paterson. Certificateless Public Key Cryptography. In *Asiacrypt'03, LNCS* 2894, pp. 452–473, 2003.
4. M.-H. Au, Q. Huang, J.-K. Liu, W. Susilo, D.-S. Wong, G. Yang. Traceable and Retrievable Identity-Based Encryption. In *ACNS'08, LNCS* 5037, pp. 94–110, 2008.
5. D. Boneh, X. Boyen. Efficient Selective-ID Secure Identity-Based Encryption Without Random Oracles. In *Eurocrypt'04, LNCS* 3027, pp. 223–238, 2004.
6. D. Boneh, X. Boyen. Secure Identity-Based Encryption Without Random Oracles. In *Crypto'04, LNCS* 3152, pp. 443–459, 2004.
7. D. Boneh, X. Boyen, E.-J. Goh. Hierarchical Identity-Based encryption with Constant Size Ciphertext. In *Eurocrypt'05, LNCS* 3494, pp. 440–456, 2005.
8. D. Boneh, M. Franklin. Identity-Based Encryption from the Weil Pairing. In *SIAM Journal of Computing* 32(3), pp. 586–615, 2003, earlier version in *Crypto'01, LNCS* 2139, pp. 213–229, 2001.
9. D. Boneh, C. Gentry, M. Hamburg. Space-Efficient Identity-Based Encryption Without Pairings. In *FOCS'07*, pp. 647–657, 2007.
10. D. Boneh, M. Hamburg. Generalized Identity Based and Broadcast Encryption Schemes. In *Asiacrypt'08, LNCS* 5350, pp. 455–470, 2008.
11. D. Boneh, J. Katz. Improved Efficiency for CCA-Secure Cryptosystems Built Using Identity-Based Encryption. In *CT-RSA'05, LNCS* 3376, pp. 87–103, 2005.
12. X. Boyen, Q. Mei, B. Waters. Direct Chosen Ciphertext Security from Identity-Based Techniques. in *ACM CCS'05*, pp. 320–329, 2005.
13. X. Boyen, B. Waters. Anonymous Hierarchical Identity-Based Encryption (Without Random Oracles). In *Crypto'06, LNCS* 4117, pages 290–307, 2006.
14. R. Canetti, S. Halevi, J. Katz. A Forward-Secure Public-Key Encryption Scheme. In *Eurocrypt'03, LNCS* 2656, pp. 254–271, 2003.

15. R. Canetti, S. Halevi, J. Katz. Chosen-Ciphertext Security from Identity-Based Encryption. In *Eurocrypt'04*, LNCS 3027, pp. 207–222, 2004.
16. J. H. Cheon. Security Analysis of the Strong Diffie-Hellman Problem. In *Eurocrypt'06*, LNCS 4004, pp. 1–11, 2006.
17. C. Cocks. An Identity-Based Encryption Scheme Based on Quadratic Residues. In *8th IMA International Conference*, LNCS 2260, pp. 360–363, 2001.
18. R. Cramer, V. Shoup. A Practical Public-Key Cryptosystem Provably Secure Against Adaptive Chosen Ciphertext Attack. In *Crypto'98*, LNCS 1462, pp. 13–25, 1998.
19. R. Cramer, V. Shoup. Universal Hash Proofs and a Paradigm for Adaptive Chosen Ciphertext Secure Public-Key Encryption. In *Eurocrypt'02*, LNCS 2332, pp. 45–64, 2002.
20. C. Gentry. Certificate-Based Encryption and the Certificate Revocation Problem. In *Eurocrypt'03*, volume 2656 of LNCS, pp. 272–293, 2003.
21. C. Gentry. Practical Identity-Based Encryption Without Random Oracles. In *Eurocrypt'06*, LNCS 4004, pp. 445–464, 2006.
22. C. Gentry, B. Waters. Adaptive Security in Broadcast Encryption Systems (with Short Ciphertexts). In *Eurocrypt'09*, LNCS 5479, pp. 171–188, 2009.
23. C. Gentry, A. Silverberg. Hierarchical ID-Based Cryptography. In *Asiacrypt'02*, LNCS 2501, pp. 548–566, 2002.
24. V. Goyal. Reducing Trust in the PKG in Identity-Based Cryptosystems. In *Crypto'07*, LNCS 4622, pp. 430–447, 2007.
25. V. Goyal, S. Lu, A. Sahai, B. Waters. Black-Box Accountable Authority Identity Based Encryption. In *ACM-CCS'08*, 2008.
26. V. Goyal, O. Pandey, A. Sahai, B. Waters. Attribute-based encryption for fine-grained access control of encrypted data. In *ACM CCS'06*, pp. 89–98, 2006.
27. D. Hofheinz, E. Kiltz. Secure Hybrid Encryption from Weakened Key Encapsulation. In *Crypto'07*, LNCS 4622, pp. 553–571, 2007.
28. A. Kiayias, M. Yung. Traitor Tracing with Constant Transmission Rate. In *Eurocrypt'02*, LNCS 2332, pp. 450–465, 2002. Updated version available as Cryptology ePrint Archive: Report 2006/458, 2006.
29. E. Kiltz, Y. Vahlis. CCA2 Secure IBE: Standard Model Efficiency through Authenticated Symmetric Encryption In *CT-RSA'08*, LNCS 4964, pp. 221–238, 2008.
30. K. Kurosawa, Y. Desmedt. A New Paradigm of Hybrid Encryption Scheme. In *Crypto'04*, LNCS 3152, pp. 445–456, 2004.
31. B. Libert, D. Vergnaud. Towards Black-Box Accountable Authority IBE with Short Ciphertexts and Private Keys. In *PKC'09*, LNCS 5443, pp. 235–255, 2009.
32. D. Naccache, A. Shamir, J.-P. Stern. How to Copyright a Function. In *PKC'99*, LNCS 1560, pp. 188–196, 1999.
33. T. Okamoto. Provably Secure and Practical Identification Schemes and Corresponding Signature Schemes. In *Crypto'92*, LNCS 740, pp. 31–53, 2002.
34. T. Pedersen. Non-Interactive and Information-Theoretic Secure Verifiable Secret Sharing. In *Crypto'91*, LNCS 576, pp. 129–140, 1991.
35. A. Sahai, B. Waters. Fuzzy Identity-Based Encryption. In *Eurocrypt'05*, LNCS 3494, pp. 457–473, 2005.
36. R. Sakai, M. Kasahara. ID-based Cryptosystems with Pairing on Elliptic Curve. In *SCIS'03*, <http://eprint.iacr.org/2003/054>, 2003.
37. P. Sarkar, S. Chatterjee. Construction of a Hybrid HIBE Protocol Secure Against Adaptive Attacks. In *ProvSec'07*, LNCS 4784, pp. 51–67, 2007.
38. C. P. Schnorr. Efficient Identification and Signatures for Smart Cards. In *Crypto'89*, LNCS 435, pp. 239–252, 1989.

39. A. Shamir. Identity-Based Cryptosystems and Signature Schemes. In *Crypto'84*, LNCS 196, pp. 47–53, 1984.
40. V. Shoup, R. Gennaro. A Note on An Encryption Scheme of Kurosawa and Desmedt. Cryptology ePrint Archive: Report 2004/194, 2004.
41. B. Waters. Efficient Identity-Based Encryption Without Random Oracles. In *Eurocrypt'05*, LNCS 3494, pp. 114–127, 2005.

A A Variant with White-Box FindKey-CCA security

To achieve IND-sID-CCA2 security, we can hybridize the scheme using an authenticated symmetric encryption scheme (as defined in appendix B) as previously considered in [37, 29] in the context of identity-based encryption. The obtained variant is reminiscent of a version of Gentry's IBE described in [29] and can be proved IND-sID-CCA2 secure in a completely analogous way.

Setup: is the same as in section 3 except that the PKG now chooses two elements $Y_A, Y_B \xleftarrow{\$} \mathbb{G}$ instead of a single one Y . An authenticated symmetric encryption scheme (E, D) of keylength $\ell \in \mathbb{N}$, a secure key derivation function $KDF : \mathbb{G}_T \rightarrow \{0, 1\}^\ell$ and a target collision-resistant hash function $H : \{0, 1\}^* \rightarrow \mathbb{Z}_p^*$ are also needed. The master key is set as $\text{msk} := x$ and the global public key is $\text{mpk} := (X = g^x, h, Y_A, Y_B, Z, H, KDF, (E, D))$.

Keygen^(PKG,U) : to obtain a private key for his identity ID, a user U interacts with the PKG as follows.

1. U sends $R = h^{t_0} \cdot X^\theta$ to the PKG and proves his knowledge of the underlying pair $(t_0, \theta) \xleftarrow{\$} (\mathbb{Z}_p^*)^2$ in a witness indistinguishable fashion.
2. The PKG outputs $\perp$ if the proof is incorrect. Otherwise, it picks random values $r'_A, t_{A,1}, r'_B, t_B \xleftarrow{\$} \mathbb{Z}_p^*$ and returns

$$\begin{aligned} d'_{ID,A} &= (d'_{A,1}, d'_{A,2}, d'_{A,3}) = \left((Y \cdot R \cdot h^{t_{A,1}})^{1/x} \cdot (g^{ID} \cdot Z)^{r'_A}, X^{r'_A}, t_{A,1} \right) \\ d'_{ID,B} &= (d'_{B,1}, d'_{B,2}, d'_{B,3}) = \left((Y_B \cdot h^{t_B})^{1/x} \cdot (g^{ID} \cdot Z)^{r'_B}, X^{r'_B}, t_B \right) \end{aligned}$$

3. U computes $d_{ID,A} = (d'_{A,1}/g^\theta \cdot (g^{ID} \cdot Z)^{r''_A}, d'_{A,2} \cdot X^{r''_A}, d'_{A,3} + t_0)$ as well as $d_{ID,B} = (d'_{B,1} \cdot (g^{ID} \cdot Z)^{r''_B}, d'_{B,2} \cdot X^{r''_B}, d_{B,3})$, for randomly chosen $r''_A, r''_B \xleftarrow{\$} \mathbb{Z}_p^*$ so that

$$\begin{aligned} d_{ID,A} &= (d_{A,1}, d_{A,2}, d_{A,3}) = \left((Y_A \cdot h^{t_A})^{1/x} \cdot (g^{ID} \cdot Z)^{r_A}, X^{r_A}, t_A \right) \\ d_{ID,B} &= (d_{B,1}, d_{B,2}, d_{B,3}) = \left((Y_B \cdot h^{t_B})^{1/x} \cdot (g^{ID} \cdot Z)^{r_B}, X^{r_B}, t_B \right) \end{aligned}$$

where $t_A = t_0 + t_{A,1}$, $r_A = r'_A + r''_A$ and $r_B = r'_B + r''_B$. He checks whether $d_{ID,A}$ and $d_{ID,B}$ respectively satisfy

$$e(d_{A,1}, X) = e(Y_A, g) \cdot e(h, g)^{d_{A,3}} \cdot e(g^{ID} \cdot Z, d_{A,2}) \quad (17)$$

$$e(d_{B,1}, X) = e(Y_B, g) \cdot e(h, g)^{d_{B,3}} \cdot e(g^{ID} \cdot Z, d_{B,2}). \quad (18)$$

If so, he sets his private key as $(d_{\text{ID},A}, d_{\text{ID},B})$ and the latter belongs to the family of decryption key identified by $n_F = d_{A,3} = t_A$.

Encrypt: to encrypt m given mpk and ID , choose $s \xleftarrow{\$} \mathbb{Z}_p^*$ and compute

$$C = (C_1, C_2, C_3, C_4) = (X^s, (g^{\text{ID}} \cdot Z)^s, e(g, h)^s, \text{E}_K(m))$$

where $K = \text{KDF}(e(g, Y_A)^s \cdot e(g, Y_B)^{\kappa s})$ and $\kappa = H(C_1, C_2, C_3)$.

Decrypt: given $C = (C_1, C_2, C_3, C_4)$ and $d_{\text{ID}} = (d_{\text{ID},A}, d_{\text{ID},B})$, compute the plaintext $m = \text{D}_K(C_4)$ (which may just be $\perp$ if C_4 is not a valid authenticated encryption) using the key

$$K = \text{KDF}\left(\frac{e(C_1, d_{A,1} \cdot d_{B,1}^\kappa)}{e(C_2, d_{A,2} \cdot d_{B,2}^\kappa) \cdot C_3^{d_{A,3} + \kappa d_{B,3}}}\right) \quad (19)$$

with $\kappa = H(C_1, C_2, C_3)$.

Trace: given an alleged private key $(d_{\text{ID},A}, d_{\text{ID},B})$, with $d_{\text{ID},A} = (d_{A,1}, d_{A,2}, d_{A,3})$, for an identity ID , check the validity of d_{ID} w.r.t. ID using relations (17)-(18). If valid, the key is declared as a member of the family $n_F = d_{3,A} = t_A$.

The proof of IND-sID-CCA security is omitted here as it is a standard application of the technique used in [29], which in turn borrows ideas from [30, 40, 27].

In the chosen-ciphertext scenario, the white-box FindKey security is no longer unconditional but relies on the (weak) ciphertext integrity property of the symmetric encryption scheme.

Theorem 12. *The scheme is FindKey-CCA secure assuming the security of the key derivation function and the (weak) ciphertext integrity of the symmetric encryption scheme. The advantage of an adversary $\mathcal{A}$ making at most q_d decryption queries is bounded by*

$$\begin{aligned} \text{Adv}_{\mathcal{A}}^{\text{FindKey-CCA}}(\lambda, \ell) &\leq 2 \cdot q_d \cdot \text{Adv}^{\text{CT-INT}}(\ell) \\ &\quad + 2 \cdot q_d \cdot \text{Adv}^{\text{KDF}}(\lambda, \ell) + \frac{2q_d^2 + q_d + 1}{p}. \end{aligned}$$

Proof. Given in appendix C. □

B Authenticated Symmetric Encryption

A symmetric encryption scheme is specified by a pair (E, D) , where E is the encryption algorithm and D is the decryption procedure, and a key space $\mathcal{K}(\ell)$ where $\ell \in \mathbb{N}$ is a security parameter. The security of authenticated symmetric encryption is defined by means of two games that capture the ciphertext indistinguishability and ciphertext (one-time) integrity properties.

Definition 6. *A symmetric encryption scheme is secure in the sense of authenticated encryption if any PPT adversary has negligible advantage in the following games.*

1. **The IND-SYM game.** For any PPT algorithm $\mathcal{A}$, the model considers the following game, where $\ell \in \mathbb{N}$ is a security parameter:

Game $_{\mathcal{A}}^{\text{IND-SYM}}(\ell)$

$$\begin{aligned}
&K \xleftarrow{\$} \mathcal{K}(\ell) \\
&(m_0, m_1, s) \leftarrow \mathcal{A}(\text{find}, \ell) \\
&d^* \xleftarrow{\$} \{0, 1\} \\
&c^* \leftarrow \text{E}_K(m_{d^*}) \\
&d \leftarrow \mathcal{A}(\text{guess}, s, c^*) \\
&\text{return } 1 \text{ if } d = d^* \text{ and } 0 \text{ otherwise.}
\end{aligned}$$

$\mathcal{A}$'s advantage is $\text{Adv}_{\mathcal{A}}^{\text{IND-SYM}}(\ell) = |\Pr[\text{Game}_{\mathcal{A}}^{\text{IND-SYM}} = 1] - 1/2|$.

2. **The CT-INT game.** Let $\mathcal{A}$ be a PPT algorithm. We consider the following game, where $\ell \in \mathbb{N}$ is a security parameter:

Game $_{\mathcal{A}}^{\text{CT-INT}}(\ell)$

$$\begin{aligned}
&K \xleftarrow{\$} \mathcal{K}(\ell) \\
&(m, s) \leftarrow \mathcal{A}(\text{find}, \ell) \\
&c \leftarrow \text{E}_K(m) \\
&c' \leftarrow \mathcal{A}(\text{create}, \ell, c) \\
&\text{return } 1 \text{ if } c' \neq c \text{ and } \text{D}_K(c') \neq \perp \\
&0 \text{ otherwise.}
\end{aligned}$$

$\mathcal{A}$'s advantage is now defined as $\text{Adv}_{\mathcal{A}}^{\text{CT-INT}}(\ell) = \Pr[\text{Game}_{\mathcal{A}}^{\text{CT-INT}} = 1]$.

The notion of weak ciphertext integrity is defined in the same way but the adversary is not allowed to see an encryption c under the challenge key K .

C Proof of Theorem 12

The proof proceeds with a sequence of two games, in which S_i denotes the event that the adversary $\mathcal{A}$ wins during Game_i with $i \in \{0, 1\}$.

Game $_0$: is the FindKey-CCA experiment. The dishonest PKG $\mathcal{A}$ generates the master public key, chooses an identity ID that she wishes to be challenged upon. She interacts with the challenger in a key generation protocol, upon completion of which the challenger $\mathcal{B}$ obtains a decryption key consisting of two triples $d_{\text{ID},A}^{(1)} = (d_{A,1}^{(1)}, d_{A,2}^{(1)}, d_{A,3}^{(1)})$, $d_{\text{ID},B}^{(1)} = (d_{B,1}^{(1)}, d_{B,2}^{(1)}, d_{B,3}^{(1)})$ that should pass the key sanity check (otherwise, $\mathcal{B}$ aborts). At this stage, $\mathcal{A}$ knows $t_B^{(1)} = d_{B,3}^{(1)}$ but has no information on $d_{A,3}^{(1)} = t_A^{(1)}$ or on the values $r_A = \log_X(d_{A,2}^{(1)})$ and $r_B = \log_X(d_{B,2}^{(1)})$ (by the construction of the key generation protocol). In the next phase, $\mathcal{A}$ starts making a number of decryption queries that the challenger handles using $(d_{\text{ID},A}^{(1)}, d_{\text{ID},B}^{(1)})$. Namely, when queried

on a ciphertext $C = (C_1, C_2, C_3, C_4)$, $\mathcal{B}$ calculates

$$\psi = \frac{e(C_1, d_{A,1}^{(1)} \cdot d_{B,1}^{(1)\kappa})}{e(C_2, d_{A,2}^{(1)} \cdot d_{B,2}^{(1)\kappa}) \cdot C_3^{d_{A,3}^{(1)} + \kappa d_{B,3}^{(1)}}},$$

where $\kappa = H(C_1, C_2, C_3)$, $K = KDF(\psi)$ and $m = D_K(C_4)$ which is returned to $\mathcal{A}$ (and may be $\perp$ if C is declared invalid).

At the end of the game, $\mathcal{A}$ outputs a key $(d_{ID,A}^{(2)}, d_{ID,B}^{(2)})$ and wins if $d_{ID,A}^{(2)}$ parses into $(d_{A,1}^{(2)}, d_{A,2}^{(2)}, d_{A,3}^{(2)})$ such that $d_{A,3}^{(1)} = t_A^{(1)} = t_A^{(2)} = d_{A,3}^{(2)}$.

We note that decryption queries on well-formed ciphertexts do not reveal any information to $\mathcal{A}$ (since all well-formed keys yield the same result). We will show that, provided all ill-formed ciphertexts are rejected by $\mathcal{B}$, $\mathcal{A}$ still has negligible information on $t_A^{(1)}$ in the end of the game. For convenience, we distinguish two types of invalid ciphertexts: type I ciphertexts (C_1, C_2, C_3, C_4) are such that $\log_X(C_1) \neq \log_{F(ID)}(C_2)$ (and can be told apart from valid ones by checking if $e(C_1, F(ID)) \neq e(X, C_2)$), where $F(ID) = g^{ID} \cdot Z$, whereas type II ciphertexts are those for which $\log_X(C_1) = \log_{F(ID)}(C_2) \neq \log_{e(g,h)}(C_3)$.

Game₁: is as Game₀ but $\mathcal{B}$ rejects all type I invalid ciphertexts (that are publicly recognizable). Such a malformed ciphertext comprises elements $C_1 = X^{s_1}$, $C_2 = F(ID)^{s_1 - s'_1}$ and $C_3 = e(g, h)^{s_1 - s'_1}$ where $s'_1 > 0$ and $s''_1 \geq 0$. Hence, the symmetric key K that $\mathcal{B}$ calculates is derived from

$$\psi = e(g, Y_A^{s_1} \cdot Y_B^{\kappa s_1}) \cdot e(F(ID), X)^{s'_1(r_A + \kappa r_B)} \cdot e(g, h)^{s''_1(t_A^{(1)} + \kappa t_B^{(1)})} \quad (20)$$

where $\kappa = H(C_1, C_2, C_3)$. Upon termination of the key generation protocol, $\mathcal{A}$ has no information on r_A, r_B (as $\mathcal{B}$ re-randomizes its key). Even if κ was the same in all decryption queries (which may happen if these queries all involve identical (C_1, C_2, C_3)), the second term of the product (20) remains almost uniformly random to $\mathcal{A}$ at each new query. Indeed, for each failed one, $\mathcal{A}$ learns at most one value that is not $r_A + \kappa r_B$. After i attempts, $p - i$ candidates are left and the distance between the uniform distribution on $\mathbb{G}_T$ and that of $e(F(ID), X)^{s'_1(r_A + \kappa r_B)}$ becomes at most $i/p \leq q_d/p$. Then, the only way for $\mathcal{A}$ to cause the new rejection rule to apply is to forge a symmetric authenticated encryption for an essentially random key K . A standard argument shows that, throughout all queries, the probability of $\mathcal{B}$ not rejecting a type I ciphertext is smaller than $q_d \cdot (\mathbf{Adv}^{\text{CT-INT}}(\ell) + \mathbf{Adv}^{\text{KDF}}(\lambda, \ell) + q_d/p)$. It easily comes that $|\Pr[S_1] - \Pr[S_0]| \leq q_d \cdot (\mathbf{Adv}^{\text{CT-INT}}(\lambda) + \mathbf{Adv}^{\text{KDF}}(\lambda, \ell) + q_d/p)$.

We now consider type II invalid queries. While $\mathcal{A}$ knows $t_B^{(1)}$, she has initially no information on $t_A^{(1)}$ and the last term of the product (20) is unpredictable to her at the first type II query. Each such rejected query allows $\mathcal{A}$ to rule out at most one candidate as for the value $t_A^{(1)}$. After $i \leq q_d$ unsuccessful type II queries, she is left with at least $p - i$ candidates at the next type II query, where the distance between the uniform distribution on $\mathbb{G}_T$ and that of ψ (calculated as per (20)) becomes smaller than $i/p \leq q_d/p$. Again, one can show that,

throughout all queries, the probability of $\mathcal{B}$ not rejecting a type II ciphertext is at most $q_d \cdot (\mathbf{Adv}^{\text{CT-INT}}(\ell) + \mathbf{Adv}^{\text{KDF}}(\lambda, \ell) + q_d/p)$. Let us call **type-2** the latter event. If all invalid ciphertexts are rejected, $\mathcal{A}$'s probability of success is given by $\Pr[S_1 | \neg \text{type-2}] \leq 1/(p - q_d) \leq (q_d + 1)/p$. Since

$$\begin{aligned}
\Pr[S_1] &= \Pr[S_1 \wedge \text{type-2}] + \Pr[S_1 \wedge \neg \text{type-2}] \\
&\leq \Pr[\text{type-2}] + \Pr[S_1 | \neg \text{type-2}] \Pr[\neg \text{type-2}] \\
&\leq \Pr[\text{type-2}] + \Pr[S_1 | \neg \text{type-2}] \\
&\leq q_d \cdot (\mathbf{Adv}^{\text{CT-INT}}(\ell) + \mathbf{Adv}^{\text{KDF}}(\lambda, \ell) + \frac{q_d}{p}) + \frac{q_d + 1}{p}
\end{aligned}$$

and $|\Pr[S_0] - \Pr[S_1]| \leq q_d \cdot (\mathbf{Adv}^{\text{CT-INT}}(\lambda) + \mathbf{Adv}^{\text{KDF}}(\lambda, \ell) + q_d/p)$, the claimed upper bound follows. $\square$